Material Safety Data Sheet



Heavy duty antifreeze

1. Product and company identification

Product name : Heavy duty antifreeze

Manufactured/supplied : 9355,Henri-Bourassa-Est

Qc,Montréal H1E 1P4

Tel: 514-643-1917

Code : 995-142 **Validation date** : 2010-10-27.

Validated by: : Whims Departement

In case of Emergency CANUTEC (613) 996-6666

Product type : Liquid.

2. Hazards identification

Physical state : Liquid.
Odor : Mild

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Emergency overview: WARNING!

CAUSES EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE

TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Precautions : Do not breathe vapor or mist. Do not get on skin or clothing. Avoid contact with eyes.

Use only with adequate ventilation. Keep container tightly closed and sealed until ready

for use. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Inhalation: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

Skin : Irritating to skin.

Eyes : Irritating to eyes.

Potential chronic health effects

Chronic effects : Contains material that may cause target organ damage, based on animal data.

Carcinogenicity:

No known significant effects or critical hazards.

No known significant effects or critical hazards.

Teratogenicity:
No known significant effects or critical hazards.

No known significant effects or critical hazards.

No known significant effects or critical hazards.

Fertility effects:
No known significant effects or critical hazards.

Target organs : Contains material which may cause damage to the following organs: kidneys, liver,

upper respiratory tract, skin, eyes, central nervous system (CNS).

Over-exposure signs/symptoms

Skin : Adverse symptoms may include the following:

irritation redness

Eyes: Adverse symptoms may include the following:

pain or irritation

watering redness

Powered by

2. Hazards identification

Medical conditions aggravated by overexposure Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3. Composition/information on ingredients

| Name | CAS number | % |
|-----------------------|------------|--------|
| 1,2-Ethanediol | 107-21-1 | 60-100 |
| Ethanol, 2,2'-oxybis- | 111-46-6 | 1-5 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical

attention if irritation occurs.

Skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention if irritation occurs.

Inhalation : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention

immediately.

Ingestion : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If potentially

dangerous quantities of this material have been swallowed, call a physician immediately.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician : No specific treatment. Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product : In a fire or if heated, a pressure increase will occur and the container may burst.

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable : |

: None known.

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:

carbon dioxide carbon monoxide phosphorus oxides metal oxide/oxides

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

995142 **2/7**



6. Accidental release measures

Personal precautions

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

 Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Canada

| Occupational exposure limits | | TWA (8 hours) | | STEL (15 mins) | | Ceiling | | | | | |
|---------------------------------------|---|-----------------------|-----------------------------|------------------|-----------------------------------|---------------------------------|-------|-----|----------------------------------|-------------|---------------------------------|
| Ingredient | List name | ppm | mg/m³ | Other | ppm | mg/m³ | Other | ppm | mg/m³ | Other | Notations |
| 1,2-Ethanediol Ethanol, 2,2'-oxybis- | US ACGIH 1/2008 AB 6/2008 BC 6/2008 ON 6/2008 QC 6/2008 US AIHA 1/2008 | - - - - - | - - 10 - - - | - - - - | - - - - 50 - 50 | - 100 20 - - 127 | - | | 100 100 - - - 100 | - - - | [a] [b] [a] [c] [d] |

Form: [a]Aerosol [b]aerosol [c]Particulate [d]Vapour [e]vapour and mist

Consult local authorities for acceptable exposure limits.

995142 **3/7**



8. Exposure controls/personal protection

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

Physical state : Liquid.

Flash point : Closed cup: 119°C (246,2°F) [Setaflash.]

Flammable limits : Lower: 3,2% Upper: 15,3%

Color : Green.
Odor : Mild
pH : 10,5 to 11

Boiling/condensation point : 171 to 175 $^{\circ}$ C (339,8 to 347 $^{\circ}$ F)

Melting/freezing point : -18° (-0,4°F)

Relative density : 1,12

Vapor pressure : <0,013 kPa (<0,1 mm Hg)

 Vapor density
 : 2,1 [Air = 1]

 Volatility
 : 97% (v/v)

Odor threshold : Not available.

Evaporation rate : Not available.

VOC content : 0 g/l

995142 **4/7**Powered by

Stability and reactivity

Chemical stability : The product is stable. Conditions to avoid No specific data. **Materials to avoid** No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Toxicological information 11.

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-------------|---------|-------------|----------|
| 1,2-Ethanediol | LD50 Oral | | 4700 mg/kg | - |
| Ethanol, 2,2'-oxybis- | LD50 Dermal | Rabbit | 11890 mg/kg | - |
| | LD50 Oral | Rat | 12000 mg/kg | - |

Conclusion/Summary

Chronic toxicity

: Not available.

Conclusion/Summary

: Not available.

Irritation/Corrosion

Conclusion/Summary

: Not available.

Sensitizer

Conclusion/Summary

: Not available.

Carcinogenicity

Conclusion/Summary

: Not available.

Classification

| Product/ingredient name | ACGIH | IARC | EPA | NIOSH | NTP | OSHA |
|-------------------------|-------|------|-----|-------|-----|------|
| 1,2-Ethanediol | A4 | - | - | - | - | - |

Mutagenicity

Conclusion/Summary

: Not available.

Teratogenicity

Conclusion/Summary

: Not available.

Reproductive toxicity

Conclusion/Summary : Not available.

12. **Ecological information**

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic ecotoxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--|---|----------|
| 1,2-Ethanediol | Acute LC50 >100000 ug/L Marine water | Crustaceans - Crangon crangon - Adult | 48 hours |
| | Acute LC50 6900000 ug/L Fresh water | Daphnia - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 8050000 ug/L Fresh water | Fish - Pimephales promelas - <=7 days | 96 hours |
| | Chronic NOEC 11610000 ug/L Fresh water | Daphnia - Ceriodaphnia dubia - <=24 hours | 48 hours |
| | Chronic NOEC 6090000 ug/L Fresh water | Fish - Pimephales promelas - <=7 days | 96 hours |

995142 5/7

Heavy duty antifreeze

12. Ecological information

| Ethanol, 2,2'-oxybis- | Acute LC50 >32000000 ug/L Fresh | Fish - Gambusia affinis - Adult | 96 hours |
|-----------------------|---------------------------------|---------------------------------|----------|
| | water | | |

Conclusion/Summary

Persistence/degradability

: Not available.

: Not available.

Conclusion/Summary

Other adverse effects

: No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|------------------------|----------------|----------------------|---------|-----|-------|------------------------|
| TDG Classification | Not regulated. | - | - | - | | - |
| IMDG Class | Not regulated. | - | - | - | | - |
| IATA-DGR Class | Not regulated. | - | - | - | | - |

PG* : Packing group

15. Regulatory information

Canada

WHMIS (Canada) : Class D-2A: Material causing other toxic effects (Very toxic).



Canadian lists

Canadian NPRI The following components are listed: Ethylene glycol

CEPA Toxic substances None of the components are listed.

Canada inventory At least one component is not listed in DSL but all such components are listed in NDSL.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

995142 6/7



16. Other information

Label requirements

: CAUSES EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of issue : 2010-10-27.

Date of previous issue : No previous validation.

Version : 0.02

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

995142 7/7

