

### Safety Data Sheet I. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	PRTMASTER 15W40	C <b>J4 12/1</b>	
Product Code:	PMW554PL		
Supplier:	Warren Distribution, Inc.		
	727 S. 13th Street		
	Omaha, NE 68102		
Phone Number:	+01 (800) 825-1235	+01 (402) 341-9397	
Emergency Phone:	CHEMTREC: +1 (800) 424-9300		
	International: +01 (703) 527-3887		
Date of Preparation:	1/22/2015 4:19:27 PM		

#### **II. HAZARDS IDENTIFICATION**

Acute Health Effects:	
<b>Routes of Entry:</b>	Skin contact, Inhalation, Ingestion, Eye contact, Absorption
Target Organs:	Lungs
Inhalation:	Breathing oil mist in concentrations that exceed the TLV and PEL may result in respiratory discomfort and irritation.
Skin Contact:	Can cause minor skin irritation, defatting, and dermatitis.
Skin Absorption:	No absorption hazard in normal industrial use.
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion:	Mildly irritating to mouth, throat, and stomach. Can cause abdominal discomfort.
<b>Chronic Health Effects:</b>	
Carcinogenicity:	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
Reproductive Toxicity:	No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Potential Health Effects:	See Section 11 for more information.
Medical Conditions Aggravated by Exposure:	Personnel with pre-existing skin disorders should avoid contact with this product., Lung disease

#### III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	Range %
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	60 - 90
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	7 - 13
Amines, polyethylenepoly-, reaction products with Succinic anhydride	84605-20-9	3 - 7
polyisobutenyl derivitives		
Polybutene	9003-29-6	0.5 - 1.5
Components not listed are not physical or health hazards as defined in 29 C	CFR 1910.1200 (Ha	zard Communication
Standard).		

	2160 KL5
Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer
Eye Contact:	oxygen. Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate

er. Get medical attention if irritation develops or persists. Seek
oms persist.
swallowed. Do not induce vomiting. Seek medical attention
edical care provider with this SDS.
wing or vomiting may severely damage the lungs. If evacuation
ecessary, use method least likely to cause aspiration.
,

V.	FIRE	FIGHTIN	G MEASURES	

Flammability:	Combustible at elevated temperatures
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water
	or foam may cause frothing if liquid is burning but it still may be a useful extinguishing
	agent if carefully applied to the surface of the fire. Do not direct a stream of water into
	the hot burning liquid.
Fire and/or Explosion	Material may be ignited only if preheated to temperatures above the high flash point, for
Hazards:	example in a fire.
Fire Fighting Methods	Do not enter fire area without proper protection including self- contained breathing
and Protection:	apparatus and full protective equipment. Use methods for the surrounding fire.
Hazardous	Carbon monoxide, Smoke
<b>Combustion Products:</b>	

### VI. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	No health affects expected from the clean up of this material if contact can be avoided.		
and Equipment:	Follow personal protective equipment recommendations found in Section 8 of this SDS.		
Methods for Cleanup:	Prevent the spread of any spill to minimize harm to human health and the environment if		
	safe to do so. Wear complete and proper personal protective equipment following the		
	recommendation of Section 8 at a minimum. Dike with suitable absorbent material like		
granulated clay. Dispose of according to Federal, State, Local, or Provincial regula			
	Used fluid should be disposed of at a recycling center. Remove from water surface by		
	skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm		
	sewers and ditches that lead to waterways. Do not flush to sewer.		

#### VII. HANDLING AND STORAGE

VII. HANDLING AND STORAGE		
Handling:	Mildly irritating material. Avoid unnecessary exposure.	
Storage:	Store in a cool dry place. Isolate from incompatible materials.	
VIII. EXPOSURE CON	TROLS/PERSONAL PROTECTION	
Engineering Controls:	Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.	
Respiratory	Respiratory protection may be required to avoid overexposure when handling this	
Protection:	product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.	
Respirator Type(s):	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.	
Eye/Face Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.	
Skin Protection:	Where use can result in skin contact, practice good personal hygiene and wear impervious gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.	
Gloves:	Neoprene, Nitrile	

Chemical Name	Occupational Exposure Limits	Value
Oil mist, mineral	OSHA PEL	5 mg/m3

Chemical Name	Occupational Exposure Limits	Value
Oil mist, mineral	OSHA PEL	5 mg/m3
Oil mist, mineral	ACGIH TLV-TWA	5 mg/m3
Oil mist, mineral	ACGIH TLV-TWA	5 mg/m3
Oil mist, mineral	ACGIH STEL	10 mg/m3
Oil mist, mineral	ACGIH STEL	10 mg/m3

#### IX. PHYSICAL AND CHEMICAL PROPERTIES

	0112011011211001
Physical State:	Liquid
Colour:	Amber
Odour:	Mild
pH:	Not determined
Viscosity (cSt at	118.8
40°C):	
Solubility:	Negligible; 0-1%
Water/Oil Partition	Not determined
<b>Coefficient:</b>	
<b>Evaporation Rate:</b>	Not determined
Vapor Density:	Not determined
Vapor Pressure:	< 0.20
Boiling Point (°C):	Not determined
Freezing Point (°C):	Not determined
Specific Gravity:	0.88
Bulk Density:	7.3 Lbs/Gallon

#### X. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
<b>Conditions to Avoid:</b> Temperatures above the high flash point of this combustible material in combin sparks, open flames, or other sources of ignition. Moisture (will lead to product	
	performance degradation).
Materials to Avoid:	Strong oxidizing agents
Hazardous	Carbon monoxide, Smoke, Carbon monoxide, sulfur oxides, aldehydes, and other
Decomposition	petroleum decomposition products in the case of incomplete combustion. Oxides of
Products:	nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present.

#### XI. TOXICOLOGICAL INFORMATION

Routes of Entry:	Skin contact, Inhalation, Inge	Skin contact, Inhalation, Ingestion, Eye contact, Absorption		
Ingestion:	Although this product has a low order of acute oral toxicity, aspiration of minute amount			
	into the lungs during ingestic	on or vomiting may cause mild to severe pulmonary injury		
	and possibly death.			
Inhalation:	No hazard in normal industri	No hazard in normal industrial use.		
Absorption:	No absorption hazard in norm	No absorption hazard in normal industrial use.		
Eye:	Upon prolonged or repeated	Upon prolonged or repeated contact, can cause moderate irritation, tearing and reddening,		
	but not likely to permanently injure eye tissue.			
Skin:	Upon prolonged or repeated	contact, can cause minor skin irritation, defatting, and		
	dermatitis.			
Chemical Name		LD50 and LC50		
Distillates (petroleum	), hydrotreated heavy paraffinic	Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg		
Polybutene		oral LD50 rat >2000 mg/kg; dermal LD50 rat >2000 mg/kg		
Target Organs:	Lungs			

Carcinogenicity:	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and
	is not considered a carcinogen by the International Agency for Research on Cancer.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is
	mutagenic or genotoxic.
Reproductive	Not known or reported to cause reproductive or developmental toxicity.
Toxicity:	
Skin Sensitization:	No data available to indicate product or components may be a skin sensitizer.

Chemical Listed as Carcinogen or Potential Carcinogen	Source Agency	
Not applicable	ACGIH- Threshold Limit Values-	
	Carcinogens	
Not applicable	IARC Carcinogen	
Known Human Carcinogen	NTP- Report on Known Human	
	Carcinogens	
Not applicable	NTP- Report on Reasonably Anticipated	
	to be Human Carcinogens	
Not applicable	U.S OSHA - Hazard Communication	
	Carcinogens	

#### XII. ECOLOGICAL INFORMATION

mi leologicile			
Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.		
Mobility:	This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.		
Persistence:	Biodegradation, adsorption to sediment, and bioconcentration to aquatic organisms should not be significant.		
Bioconcentration: Degradability:	Bioconcentration may occur. Biodegrades slowly.		
Degrauability.	Dioucgraues slowry.		

#### XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging:Recycle containers whenever possible.Disposal Methods:Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil.

#### XIV. TRANSPORTATION INFORMATION

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

#### **XV. REGULATORY INFORMATION**

Chemical Name	Regulation	CAS #	% Range
None.	CERCLA RQ		-
Diphenylamine	SARA 313	122-39-4	0.01 - 0.1
Ethylene glycol	SARA 313	107-21-1	0.01 - 0.1
Vinyl acetate	SARA 313	108-05-4	0.001-0.01
Benzene	SARA 313	71-43-2	<10ppm
None.	SARA 302-EHS		
Benzene	CA Prop 65 – Cancer	71-43-2	<10ppm
Benzene	CA Prop 65 - Dev.	71-43-2	<10ppm
	Toxicity		
None.	CA Prop 65 - Reprod		
	–fem		
Benzene	CA Prop 65 - Reprod	71-43-2	<10ppm
	-male		

Polybutene	Canadian WHMIS List	9003-29-6	0.5 - 1.5
Inventory- U.S. TSCA: All con	nponents of this material are on t	he US TSCA Ir	nventory or are exempt.
OSHA Hazard Classification:Lung toWHMIS Classification:D2BInventory- Canada DomesticPresentSubstance List:PresentInventory- Canada Non-PresentDomestic Substance List:Present			

	HMI	<u>S Ra</u>	<u>tings:</u> <u>N</u>	FPA Rat	<u>ings:</u>
Health:		1	Health:	1	
Fire:		1	Fire:	1	
Reactiv	ity:	0	Reactivity:	0	
PPE:		В			
KEY:	0 - L	east	1 - Slight 2 - Moderate	3 - High	4 – Extreme

#### XVI. ADDITIONAL INFORMATION

Superseded by:	None
Revision Date:	1/22/2015 4:19:27 PM
Prepared by:	TPRUETT
References:	ACGIH: American Conference of Governmental Industrial Hygienists
	AIHA: American Industrial Hygiene Association
	CFR: Code of Federal Regulations
	DOT: United States Department of Transportation
	GHS: Globally Harmonized System of Classification and Labeling of Chemicals
	HMIS: Hazardous Materials Identification System
	IARC: International Agency for Research on Cancer
	IATA: International Air Transportation Association
	IDLH: Immediately Dangerous to Life or Health
	IMDG: International Maritime Dangerous Goods
	NFPA: National Fire Protection Association
	NIOSH: National Institute for Occupational Safety and Health
	NTP: National Toxicology Program
	OSHA: Occupational Safety and Health Administration
	PEL: Permissible Exposure Limit
	RTK: Right-to-Know
	SARA: Superfund Amendments and Reauthorization Act
	STEL: Short-term Exposure Limit
	TLV: Threshold limit value
	TSCA: Toxic Substances Control Act
	TWA: Time weighted average
	UN: United Nations
	WHMIS: Workplace Hazardous Materials Information System
Disclaimer:	This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.