

## I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PARTS MASTER 10w30 CJ4 5

Product Code: PMW2135G

**Supplier:** AGCO Corporation

4205 River Green Parkway

Duluth, GA 30096

**Phone Number:** +1(770) 813-9200

**Emergency Phone:** CHEMTREC: +1 (800) 424-9300

International: +01 (703) 527-3887

**Date of Preparation:** 1/22/2015 4:06:06 PM

## II. HAZARDS IDENTIFICATION

**Acute Health Effects:** 

**Routes of Entry:** Skin contact, Inhalation, Ingestion, Eye contact, Absorption

Target Organs: Lungs

**Inhalation:** Breathing oil mist in concentrations that exceed the TLV and PEL may result in

respiratory discomfort and irritation.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Skin Absorption:** No absorption hazard in normal industrial use.

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to permanently

injure eye tissue.

**Ingestion:** Mildly irritating to mouth, throat, and stomach. Can cause abdominal discomfort.

**Chronic Health Effects:** 

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and

is not considered a carcinogen by the International Agency for Research on Cancer.

**Reproductive** No data available to indicate product or any components present at greater than 0.1%

**Toxicity:** may cause birth defects.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is

mutagenic or genotoxic.

**Potential Health** 

**Effects:** 

See Section 11 for more information.

**Medical Conditions** Personnel with pre-existing skin disorders should avoid contact with this product., Lung

**Aggravated by** disease

**Exposure:** 

#### III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Range %		
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	40 - 70		
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	10 - 30		
Amines, polyethylenepoly-, reaction products with Succinic anhydride	84605-20-9	3 - 7		
polyisobutenyl derivitives				
Polybutene	9003-29-6	0.5 - 1.5		

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

#### IV. FIRST-AID MEASURES

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual administer

oxygen.

**Eye Contact:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the

head to prevent chemical from transferring to the uncontaminated eye. Get immediate

medical attention.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or persists. Seek

medical advice if symptoms persist.

**Ingestion:** Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical attention

immediately. Provide medical care provider with this SDS.

**Notes to Doctor:** Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation

of stomach contents is necessary, use method least likely to cause aspiration.

#### V. FIRE FIGHTING MEASURES

**Flammability:** Combustible at elevated temperatures

**Extinguishing Media:** Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water

or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into

the hot burning liquid.

Fire and/or Explosion

Hazards:

Hazardous

Material may be ignited only if preheated to temperatures above the high flash point, for

example in a fire.

Fire Fighting Methods and Protection:

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

Carbon monoxide, Smoke

**Combustion Products:** 

#### VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Methods for Cleanup: No health affects expected from the clean up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS. Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center. Remove from water surface by skimming or with suitable absorbents. Do not use dispersants. Avoid runoff into storm sewers and ditches that lead to waterways. Do not flush to sewer.

## VII. HANDLING AND STORAGE

**Handling:** Mildly irritating material. Avoid unnecessary exposure. **Storage:** Store in a cool dry place. Isolate from incompatible materials.

## VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls:** Use local exhaust ventilation or other engineering controls to minimize exposures and

maintain operator comfort.

**Respiratory** Respiratory protection may be required to avoid overexposure when handling this

**Protection:** product. General or local exhaust ventilation is the preferred means of protection. Use a

respirator if general room ventilation is not available or sufficient to eliminate symptoms.

**Respirator Type(s):** None required where adequate ventilation is provided. If airborne concentrations are

above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

**Eye/Face Protection:** Wear chemically resistant safety glasses with side shields when handling this product. Do

not wear contact lenses.

**Skin Protection:** Where use can result in skin contact, practice good personal hygiene and wear

impervious gloves. Wash hands and other exposed areas with mild soap and water before

eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile

Chemical NameOccupational Exposure LimitsValueOil mist, mineralOSHA PEL5 mg/m3Oil mist, mineralOSHA PEL5 mg/m3Oil mist, mineralACGIH TLV-TWA5 mg/m3

Chemical NameOccupational Exposure LimitsValueOil mist, mineralACGIH TLV-TWA5 mg/m3Oil mist, mineralACGIH STEL10 mg/m3Oil mist, mineralACGIH STEL10 mg/m3

#### IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:LiquidColour:AmberOdour:Mild

**pH:** Not determined

Viscosity (cSt at

40°C):

76.95

**Solubility:** Negligible; 0-1% **Water/Oil Partition** Not determined

**Coefficient:** 

**Evaporation Rate:** Not determined **Vapor Density:** Not determined

**Vapor Pressure:** <0.20

**Boiling Point (°C):** Not determined **Freezing Point (°C):** Not determined

**Specific Gravity:** 0.87

**Bulk Density:** 7.23 Lbs/Gallon

## X. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

Conditions to Avoid: Temperatures above the high flash point of this combustible material in combination with

sparks, open flames, or other sources of ignition. Moisture (will lead to product

performance degradation).

Materials to Avoid: Strong oxidizing agents

**Hazardous**Carbon monoxide, Smoke, Carbon monoxide, sulfur oxides, aldehydes, and other **Decomposition**Products:
Carbon monoxide, Smoke, Carbon monoxide, sulfur oxides, aldehydes, and other
petroleum decomposition products in the case of incomplete combustion. Oxides of
nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may

also be present.

### XI. TOXICOLOGICAL INFORMATION

Routes of Entry: Skin contact, Inhalation, Ingestion, Eye contact, Absorption

Ingestion: No hazard in normal industrial use.
Inhalation: No hazard in normal industrial use.

**Absorption:** No absorption hazard in normal industrial use.

**Eve:** Upon prolonged or repeated contact, can cause moderate irritation, tearing and reddening,

but not likely to permanently injure eye tissue.

**Skin:** Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

Chemical Name LD50 and LC50

Distillates (petroleum), hydrotreated heavy paraffinic Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat

>2000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg oral LD50 rat >2000 mg/kg; dermal LD50 rat >2000

mg/kg

**Target Organs:** Lungs

Polybutene

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and

is not considered a carcinogen by the International Agency for Research on Cancer.

**Mutagenicity:** No data available to indicate product or any components present at greater than 0.1% is

mutagenic or genotoxic.

**Reproductive** Not known or reported to cause reproductive or developmental toxicity.

Toxicity:

**Skin Sensitization:** No data available to indicate product or components may be a skin sensitizer.

Chemical Listed as Carcinogen or Potential Carcinogen	Source Agency	
Not applicable	ACGIH- Threshold Limit Values-	
	Carcinogens	
Not applicable	IARC Carcinogen	
Known Human Carcinogen	NTP- Report on Known Human	
	Carcinogens	
Not applicable	NTP- Report on Reasonably Anticipated	
	to be Human Carcinogens	
Not applicable	U.S OSHA - Hazard Communication	
	Carcinogens	

## XII. ECOLOGICAL INFORMATION

Overview: Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Mobility: This material is expected to have essentially no mobility in soil. It absorbs strongly to

most soil types.

**Persistence:** Biodegradation, adsorption to sediment, and bioconcentration to aquatic organisms

should not be significant.

**Bioconcentration:** Bioconcentration may occur.

**Degradability:** Biodegrades slowly.

#### XIII. DISPOSAL CONSIDERATIONS

**Disposal of Packaging:** Recycle containers whenever possible.

**Disposal Methods**: Dispose of according to Federal, State, Local, or Provincial regulations. Recycle used oil.

## XIV. TRANSPORTATION INFORMATION

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

#### XV. REGULATORY INFORMATION

Chemical Name	Regulation	CAS#	% Range
None.	CERCLA RQ		
Diphenylamine	SARA 313	122-39-4	0.01 - 0.1
Ethylene glycol	SARA 313	107-21-1	0.01 - 0.1
Vinyl acetate	SARA 313	108-05-4	0.001- 0.01
Benzene	SARA 313	71-43-2	<10ppm
None.	SARA 302-EHS		
Benzene	CA Prop 65 – Cancer	71-43-2	<10ppm
Benzene	CA Prop 65 - Dev.	71-43-2	<10ppm
	Toxicity		
None.	CA Prop 65 - Reprod		
	–fem		
Benzene	CA Prop 65 - Reprod	71-43-2	<10ppm
	–male		
Polybutene	Canadian WHMIS List	9003-29-6	0.5 - 1.5

**Inventory- U.S. TSCA:** All components of this material are on the US TSCA Inventory or are exempt.

OSHA Hazard Classification: Lung toxin - may cause lung damage

WHMIS Classification: Uncontrolled product according to WHMIS classification criteria

**Inventory- Canada Domestic** Present

**Substance List:** 

**Inventory- Canada Non-** Present

**Domestic Substance List:** 

**HMIS Ratings:** NFPA Ratings:

 Health:
 1
 Health:
 1

 Fire:
 1
 Fire:
 1

 Reactivity:
 0
 Reactivity:
 0

**PPE:** B

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme

## XVI. ADDITIONAL INFORMATION

Superseded by: None

Revision Date: 1/22/2015 4:06:06 PM

Prepared by: TPRUETT

References: ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CFR: Code of Federal Regulations

DOT: United States Department of Transportation

GHS: Globally Harmonized System of Classification and Labeling of Chemicals

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transportation Association IDLH: Immediately Dangerous to Life or Health IMDG: International Maritime Dangerous Goods NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PEL: Permissible Exposure Limit

RTK: Right-to-Know

SARA: Superfund Amendments and Reauthorization Act

STEL: Short-term Exposure Limit

TLV: Threshold limit value

TSCA: Toxic Substances Control Act

TWA: Time weighted average

**UN: United Nations** 

WHMIS: Workplace Hazardous Materials Information System

Disclaimer: This safety data sheet and the information it contains is offered to you in good faith as

accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made,

either expressed or implied.