

PRODUCT INFORMATION



Parts Master Heavy Duty SAE 5W-40 Full Synthetic Diesel Engine Oil

Description

Parts Master Heavy Duty SAE 5W-40 Full Synthetic Diesel Engine Oil is designed to provide performance and protection in modern, emissions treatment equipped diesel engines, including those with Exhaust Gas Recirculation (EGR) and Diesel Particulate Filters (DPF).

Parts Master Heavy Duty SAE 5W-40 Full Synthetic Diesel Engine Oil is licensed for API service CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4, SN, SM, and all prior API gasoline categories.

Parts Master Heavy Duty SAE 5W-40 Full Synthetic Diesel Engine Oil is recommended for applications where Cummins CES 20086, Mack EOS-4.5, Volvo VDS-4.5 Detroit Diesel DFS 93K222, Renault RLD-3, ACEA E11, ACEA E7, MB 228.31, Ford WSS-M2C171-F1, Caterpillar ECF-3 or Chrysler MS-10902 are specified.

Typical Properties

	SAE 5W-40
KV100 (cSt)	15.3
KV40 (cSt)	95.1
Viscosity Index	171
Density @ 15 °C g/m ³	0.85
Pour Point, °C	-39
HTHS (cP)	4.0
CCS (cP @ °C)	6000@ -30
Zinc, ppm	1270
Phosphorus, ppm	1150
Noack (% loss)	<11.0

See operator's manual for recommended viscosity grade and API service classification.