

ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON Canada L7G 0C6
Telephone: (800) 924-6994
Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: 09270 PC EXHAUST SYSTEM REPAIR KIT 383758 1.16 YD PART 1
Item No: PTX860485A
Product Type: Impregnated bandage

II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
FIBERGLASS YARN 65997-17-3	55-65	not available	not available	
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	30-40	11400 mg/kg	not available	
METHYL ETHYL KETONE (BUTANONE) 78-93-3	<3	2737 mg/kg	32 g/m ³ (4H)	200 ppm

III. PHYSICAL DATA

Physical State/Appearance: Clear to yellow coated fiberglass
Odour & Odour Threshold: Ketone odour
Specific Gravity: Does not apply
Evaporation Rate: Does not apply
Vapour Pressure: None
Vapour Density: Not determined
Freezing Point: Does not apply
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: Not applicable

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam
Hazardous Combustion Products: Oxides of carbon, Ketones
Sensitivity to Static Discharge: Sensitivity to static discharge is not expected
Conditions of Flammability: During a fire, irritating and toxic gases may be generated during combustion or decomposition.
Flash Point/Range: Concentrated vapors may be ignitable
Autoignition Temperature: Not determined
Upper Explosive Limit: 10.0%
Lower Explosive Limit: 1.8

V. REACTIVITY DATA

Conditions Causing Chemical Instability: Stable under normal conditions of use
Materials to avoid: Strong oxidizers, Reducing agents
Conditions of Reactivity: High temperatures.
Hazardous Decomposition Products: Carbon oxides, Ketones

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation
Existing Conditions Aggravated by Exposure: Persons with preexisting respiratory, liver, kidney, eye or skin diseases may be adversely affected
Toxicity Information: (See Effects of Acute Exposure to Product)
Effects of Acute Exposure: Harmful if swallowed. May cause eye and skin irritation.
Effects of Chronic Exposure: Overexposure to methyl ethyl ketone and n-hexane may cause peripheral nerve damage (that of arms and legs) and result in muscular weakness and loss of sensation.

VI. HAZARDS IDENTIFICATION

Irritancy of Product: Eyes: Exposure to liquid or vapor causes mild eye irritation. Symptoms may include burning, tearing, redness, stinging, blurred vision and corneal injury. May cause gastrointestinal irritation, central nervous system depression.

Sensitization to Product: (See Effects of Acute Exposure to Product)

Carcinogenicity: (See Effects of Chronic Exposure to Product)

Reproductive Toxicity: (See Effects of Chronic Exposure to Product)

Teratogenicity: (See Effects of Chronic Exposure to Product)

Mutagenicity: (See Effects of Chronic Exposure to Product)

Toxicologically Synergistic Products: None known

WHMIS Hazard Class: D2B TOXIC MATERIALS

VII. PREVENTATIVE MEASURES

Personal Protection

Eyes: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Engineering Controls: In case of insufficient ventilation, wear an organic vapor respirator

Spill Procedures: Eliminate all sources of ignition. Reclaim clean material. Contaminated material should be swept or shoveled into appropriate waste container for proper disposal.

Protection of Man and Environment: Follow Canadian and local regulations for disposal.

Handling Procedures and Equipment: Store in a dry area below 35°C.

Special Handling Information: Avoid contact with eyes. Do not take internally. Do not use for prolonged periods in confined area without adequate ventilation.

VIII. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed.

Skin Contact: Wash with soap and water. If skin irritation persists, call a physician. Remove contaminated clothing and launder before reuse.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

Proper Shipping Name: Not regulated
Hazard Class: None
UN/ID No: None

IATA (Air)

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG (Vessel)

Proper Shipping Name: Not regulated
Hazard Class: None
UN Number: None

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 2, PHYSICAL HAZARD 0
HMIS is a registered trademark of the National Paint and Coatings Association

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 2, REACTIVITY 1
(NFPA is a registered trademark of the National Fire Protection Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: February 23, 2012

Company: ITW Permatex Canada. 35 Brownridge Rd. Unit 1, Halton Hills, ON L76 0C6

Revision Number: 5

Telephone No.: 1-800-924-6994