

Permatex Canada, Inc.
 8450 Lawson Road, Unit 1
 Milton, ON Canada L9T 0A4
 Telephone: 1-87-Permatex
 (877) 376-2839
 Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: MEDIUM STRENGTH THREADLOCKER BLUE GEL 5 GR
Item No: 24005
Product Type: Anaerobic

II. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | Weight% | LD50/oral/rat | LC50/inhalation/rat | ACGIH; TLV-TWA |
|---|---------|---------------|---------------------|----------------------|
| POLYGLYCOL DIMETHACRYLATE 25852-47-5 | 30-50 | not available | not available | |
| POLYESTER RESIN MIXTURE | 20-40 | not available | not available | |
| BENZOATE ESTERS MIXTURE | <20 | not available | not available | |
| TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7 | <10 | >5,000 mg/kg | not available | 10 mg/m ³ |
| DIMETHYLBENZYL HYDROPEROXIDE 80-15-9 | <3 | 382 mg/kg | 200 ppm/4H | |
| PROPYLENE GLYCOL 57-55-6 | <3 | 20 g/kg | not available | |
| TITANIUM DIOXIDE 13463-67-7 | 0.1-1.0 | >10000 mg/kg | not available | 10 mg/m ³ |

III. PHYSICAL DATA

Physical State/Appearance: Blue gel
Odour & Odour Threshold: Mild odour
Specific Gravity: 1.11-1.15
Evaporation Rate: Not determined
Vapour Pressure: Not determined
Vapour Density: Heavier than air
Freezing Point: Not determined
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: >150°C

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam
Hazardous Combustion Products: Oxides of carbon
Sensitivity to Static Discharge: Sensitivity to static discharge is not expected.
Conditions of Flammability: None anticipated.
Flash Point/Range: >95°C COC
Autoignition Temperature: Not determined
Upper Explosive Limit: Not determined
Lower Explosive Limit: Not determined

V. REACTIVITY DATA

Conditions Causing Chemical Instability: Stable under normal conditions of use
Materials to avoid: Strong oxidizing agents
Conditions of Reactivity: High temperatures
Hazardous Decomposition Products: Carbon oxides

VI. HAZARDS IDENTIFICATION

| | |
|--|---|
| Primary Routes of Exposure: | Eye and skin contact, ingestion, inhalation |
| Existing Conditions Aggravated by Exposure: | Allergy, eczema, skin conditions |
| Toxicity Information: | (See Effects of Acute Exposure to Product) |
| Effects of Acute Exposure: | May cause eye and skin irritation. May cause allergic skin reactions and sensitization. Overexposure by inhalation may cause nasal and respiratory irritation, central nervous system affects, dizziness, drowsiness, weakness, fatigue, nausea, headache and possible unconsciousness. |
| Effects of Chronic Exposure: | May cause central nervous system effects. Note: This product does not contain microcrystalline silica. |
| Irritancy of Product: | May cause dermatitis on prolonged contact in sensitive individuals. Eyes: Exposure to liquid or vapor causes mild eye irritation. Symptoms may include burning, tearing, redness, stinging, blurred vision and corneal injury. |
| Sensitization to Product: | (See Effects of Acute Exposure to Product) |
| Carcinogenicity: | (See Effects of Chronic Exposure to Product) |
| Reproductive Toxicity: | (See Effects of Chronic Exposure to Product) |
| Teratogenicity: | (See Effects of Chronic Exposure to Product) |
| Mutagenicity: | (See Effects of Chronic Exposure to Product) |
| Toxicologically Synergistic Products: | None known |
| WHMIS Hazard Class: | D2B TOXIC MATERIALS |

VII. PREVENTATIVE MEASURES

| | |
|---|---|
| Personal Protection | |
| Eyes: | Safety glasses. |
| Skin: | Neoprene or nitrile gloves recommended. |
| Ventilation: | General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator. |
| Engineering Controls: | In case of insufficient ventilation, wear an organic vapor respirator. |
| Spill Procedures: | Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. |
| Protection of Man and Environment: | Follow Canadian and local regulations for disposal. |
| Handling Procedures and Equipment: | Store in a dry area below 35°C. |
| Special Handling Information: | Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use. |

VIII. FIRST AID MEASURES

| | |
|----------------------|---|
| Ingestion: | If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. |
| Inhalation: | Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention. |
| Skin Contact: | Wash off with soap and water. If skin irritation persists, call a physician. |
| Eye Contact: | In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists. |

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

| | |
|------------------------------|---------------|
| Proper Shipping Name: | Not regulated |
| Hazard Class: | None |
| UN/ID No: | None |

IATA

| | |
|------------------------------|---------------|
| Proper Shipping Name: | Not regulated |
| Class or Division: | None |
| UN/ID Number: | None |

IMDG

| | |
|-------------------------|---------------|
| Proper Shipping: | Not regulated |
| Hazard Class: | None |
| UN Number: | None |

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 1
HMIS is a registered trademark of the National Paint and Coatings Assn.

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0
NFPA is a registered trademark of the National Fire Protection Assn.

**Product Name: MEDIUM STRENGTH THREADLOCKER
BLUE GEL 5 GR**

Item No: 24005

X. PREPARATION INFORMATION

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: June 21, 2010

Company:
Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

Revision Number: 3

Telephone No.: 1-87-Permatex (877) 376-2839