

Permatex Canada, Inc.  
8450 Lawson Road, Unit 1  
Milton, ON Canada L9T 0A4  
Telephone: 1-87-Permatex  
(877) 376-2839  
Urgence: 800-255-3924 (ChemTel)

## Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

### I. PRODUCT IDENTIFICATION

Product Name: PC ULTRA SLICK CERAMIC EXTREME BRAKE LUBRICANT 236 ML  
Item No: 24126  
Product Type: Lubricant

### II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
SYNTHETIC BASE OILS (TRADE SECRET)	>90	not available	not available	

### III. PHYSICAL DATA

Physical State/Appearance: Purple liquid  
Odour & Odour Threshold: Mild odour  
Specific Gravity: 0.94  
Evaporation Rate: <1 (butyl acetate = 1)  
Vapour Pressure: Not determined  
Vapour Density: Heavier than air  
Freezing Point: Not determined  
pH: Does not apply  
Octanol/Water Coefficient: Not determined  
Boiling Point: Not determined

### IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.  
Hazardous Combustion Products: Oxides of carbon  
Sensitivity to Static Discharge: Sensitivity to static discharge is not expected  
Conditions of Flammability: None anticipated.  
Flash Point/Range: >260°C COC  
Autoignition Temperature: Not determined  
Upper Explosive Limit: Not determined  
Lower Explosive Limit: Not determined

### V. REACTIVITY DATA

Conditions Causing Chemical Instability: None  
Materials to avoid: Strong oxidizers  
Conditions of Reactivity: High temperatures.  
Hazardous Decomposition Products: Carbon oxides

### VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation  
Existing Conditions Aggravated by Exposure: May aggravate preexisting dermatitis  
Toxicity Information: (See Effects of Acute Exposure to Product)  
Effects of Acute Exposure: May cause eye and skin irritation.  
Effects of Chronic Exposure: None known.  
Irritancy of Product: Irritation of eyes, skin, nose and throat. May cause dermatitis on prolonged contact in sensitive individuals.  
Sensitization to Product: (See Effects of Acute Exposure to Product)  
Carcinogenicity: (See Effects of Chronic Exposure to Product)  
Reproductive Toxicity: (See Effects of Chronic Exposure to Product)  
Teratogenicity: (See Effects of Chronic Exposure to Product)  
Mutagenicity: (See Effects of Chronic Exposure to Product)

**Product Name:** PC ULTRA SLICK CERAMIC EXTREME  
BRAKE LUBRICANT 236 ML

**Item No:** 24126

## **VI. HAZARDS IDENTIFICATION**

**Toxicologically Synergistic Products:** None known  
**WHMIS Hazard Class:** Non-controlled

## **VII. PREVENTATIVE MEASURES**

### **Personal Protection**

**Eyes:** Safety glasses.  
**Skin:** Neoprene or nitrile gloves recommended.  
**Ventilation:** General ventilation is usually adequate.  
**Engineering Controls:** In case of insufficient ventilation, wear an organic vapor respirator.  
**Spill Procedures:** Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.  
**Protection of Man and Environment:** Follow Canadian and local regulations for disposal.  
**Handling Procedures and Equipment:** Use good personal hygiene. Avoid smoking, eating or drinking during use.  
**Special Handling Information:** Avoid contact with skin and eyes. This product may cause surfaces to become slippery.

## **VIII. FIRST AID MEASURES**

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Get medical attention/advice if you feel unwell.  
**Skin Contact:** Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.  
**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

## **IX. SHIPPING INFORMATION**

### **Canadian Transportation of Dangerous Goods**

**Proper Shipping Name:** Not regulated  
**Hazard Class:** None  
**UN/ID No:** None

### **IATA**

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/ID Number:** None

### **IMDG**

**Proper Shipping:** Not regulated  
**Hazard Class:** None  
**UN Number:** None

## **X. PREPARATION INFORMATION**

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0  
HMIS is a registered trademark of the National Paint and Coatings Assn.

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1 REACTIVITY 1  
NFPA is a registered trademark of the National Fire Protection Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety

**Revision Date:** May 11, 2011

**Company:**  
Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

**Revision Number:** 3

**Telephone No.:** 1-87-Permatex (877) 376-2839