

Permatex Canada, Inc.
8450 Lawson Road, Unit 1
Milton, ON Canada L9T 0A4
Telephone: 1-87-Permatex
(877) 376-2839
Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: PC PERMANENT STRENGTH THREADLOCKER RED 36ML
Item No: 26242
Product Type: Anaerobic

II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
POLYGLYCOL DIMETHACRYLATE 25852-47-5	60-80	not available	not available	
POLYESTER RESIN MIXTURE	20-40	not available	not available	
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	382 mg/kg	200 ppm/4H	

III. PHYSICAL DATA

Physical State/Appearance: Red liquid
Odour & Odour Threshold: Mild odour
Specific Gravity: 1.05
Evaporation Rate: <1 (butyl acetate = 1)
Vapour Pressure: Not determined
Vapour Density: Heavier than air
Freezing Point: Not determined
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: >150°C

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Water fog, carbon dioxide, foam, dry chemical.
Hazardous Combustion Products: Oxides of carbon
Sensitivity to Static Discharge: Sensitivity to static discharge is not expected.
Conditions of Flammability: None anticipated.
Flash Point/Range: >95°C COC
Autoignition Temperature: Not determined
Upper Explosive Limit: Not determined
Lower Explosive Limit: Not determined

V. REACTIVITY DATA

Conditions Causing Chemical Instability: None
Materials to avoid: Strong oxidizing agents, Peroxides, Reducing agents
Conditions of Reactivity: None
Hazardous Decomposition Products: Carbon oxides

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation

Existing Conditions Aggravated by Exposure: May aggravate preexisting dermatitis

Toxicity Information: (See Effects of Acute Exposure to Product)

Effects of Acute Exposure: At elevated temperatures, may cause irritation of the eyes and respiratory tract. May cause allergic skin reactions and sensitization. Moderately toxic if swallowed. Irritating to mouth, throat and stomach with nausea.

Effects of Chronic Exposure: May cause an allergic skin reaction.

VI. HAZARDS IDENTIFICATION

Irritancy of Product: May cause dermatitis on prolonged contact in sensitive individuals. May cause gastrointestinal irritation, central nervous system depression.

Sensitization to Product: (See Effects of Acute Exposure to Product)

Carcinogenicity: (See Effects of Chronic Exposure to Product)

Reproductive Toxicity: (See Effects of Chronic Exposure to Product)

Teratogenicity: (See Effects of Chronic Exposure to Product)

Mutagenicity: (See Effects of Chronic Exposure to Product)

Toxicologically Synergistic Products: None known

WHMIS Hazard Class: D2B TOXIC MATERIALS

VII. PREVENTATIVE MEASURES

Personal Protection

Eyes: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator.

Engineering Controls: In case of insufficient ventilation, wear an organic vapor respirator.

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

Protection of Man and Environment: Follow Canadian and local regulations for disposal.

Handling Procedures and Equipment: Store in a dry area below 35°C.

Special Handling Information: Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use.

VIII. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

Proper Shipping Name: Not regulated

Hazard Class: None

UN/ID No: None

IATA

Proper Shipping Name: Not regulated

Class or Division: None

UN/ID Number: None

IMDG

Proper Shipping: Not regulated

Hazard Class: None

UN Number: None

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0
HMIS is a registered trademark of the National Paint and Coatings Assn.

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1
NFPA is a registered trademark of the National Fire Protection Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: October 27, 2010

Company:
Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

Revision Number: 4

Telephone No.: 1-87-Permatex (877) 376-2839