

Permatex Canada, Inc.  
8450 Lawson Road, Unit 1  
Milton, ON Canada L9T 0A4  
Telephone: 1-87-Permatex  
(877) 376-2839  
Urgence: 800-255-3924 (ChemTel)

## Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

### I. PRODUCT IDENTIFICATION

**Product Name:** PC ATF RESISTANT RTV GASKET MAKER 85 GR  
**Item No:** 31870  
**Product Type:** Elastomeric rubber

### II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	30-50	>40,000 mg/kg	>535 mg/l	
LIMESTONE 1317-65-3	20-40	>5000 mg/kg	not available	
MODIFIED SILICON DIOXIDE 68611-44-9	<7	not available	not available	
POLYDIMETHYLSILOXANE 63148-62-9	<5	>17 g/kg	not available	
VINYL OXIMINOSILANE 2224-33-1	<5	not available	not available	
2-BUTANONE OXIME 96-29-7	0.5-2.0	930 mg/kg	20 mg/L/4H	

### III. PHYSICAL DATA

**Physical State/Appearance:** Black paste  
**Odour & Odour Threshold:** Mild odour  
**Specific Gravity:** 1.36  
**Evaporation Rate:** Not determined  
**Vapour Pressure:** <5 mmHg @ 21°C  
**Vapour Density:** Approximately 3  
**Freezing Point:** Not determined  
**pH:** Does not apply  
**Octanol/Water Coefficient:** Not determined  
**Boiling Point:** Not applicable, Polymeric

### IV. FIRE AND EXPLOSIVE DATA

**Recommended Extinguishing Media:** Carbon Dioxide, Dry Chemicals, Foam.  
**Hazardous Combustion Products:** Oxides of nitrogen, methyl ethyl ketone, possibly methyl ethyl ketoxime., Formaldehyde, silica fume, oxides of carbon  
**Sensitivity to Static Discharge:** Sensitivity to static discharge is not expected  
**Conditions of Flammability:** None anticipated.  
**Flash Point/Range:** >95°C COC  
**Autoignition Temperature:** Not determined  
**Upper Explosive Limit:** Not determined  
**Lower Explosive Limit:** Not determined

### V. REACTIVITY DATA

**Conditions Causing Chemical Instability:** None  
**Materials to avoid:** Polymerization can occur, Water, iron, acids  
**Conditions of Reactivity:** None.  
**Hazardous Decomposition Products:** Methyl ethyl ketoxime, Silicon oxides, Oxides of nitrogen, Formaldehyde

### VI. HAZARDS IDENTIFICATION

**Primary Routes of Exposure:** Eye and skin contact, ingestion, inhalation  
**Toxicity Information:** (See Effects of Acute Exposure to Product)

## **VI. HAZARDS IDENTIFICATION**

<b>Effects of Acute Exposure:</b>	May cause eye and skin irritation. Moderately toxic if swallowed. Irritating to mouth, throat and stomach with nausea. When this product is exposed to moisture, 2-Butanone oxime may be formed.
<b>Effects of Chronic Exposure:</b>	None known.
<b>Irritancy of Product:</b>	2-Butanone oxime vapors produced during cure are toxic and irritate eyes, nose and throat.
<b>Sensitization to Product:</b>	<b>(See Effects of Acute Exposure to Product)</b>
<b>Carcinogenicity:</b>	<b>(See Effects of Chronic Exposure to Product)</b>
<b>Reproductive Toxicity:</b>	<b>(See Effects of Chronic Exposure to Product)</b>
<b>Teratogenicity:</b>	<b>(See Effects of Chronic Exposure to Product)</b>
<b>Mutagenicity:</b>	<b>(See Effects of Chronic Exposure to Product)</b>
<b>Toxicologically Synergistic Products:</b>	None known
<b>WHMIS Hazard Class:</b>	D2B TOXIC MATERIALS

## **VII. PREVENTATIVE MEASURES**

### **Personal Protection**

<b>Eyes:</b>	Safety glasses. Avoid contact lenses..
<b>Skin:</b>	Neoprene or nitrile gloves recommended.
<b>Ventilation:</b>	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator.
<b>Engineering Controls:</b>	In case of insufficient ventilation, wear an organic vapor respirator.
<b>Spill Procedures:</b>	Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.
<b>Protection of Man and Environment:</b>	Follow Canadian and local regulations for disposal.
<b>Handling Procedures and Equipment:</b>	Store in a dry area below 35°C. Keep container closed when not in use.
<b>Special Handling Information:</b>	Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use.

<b>Comments:</b>	When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde
------------------	---

## **VIII. FIRST AID MEASURES**

<b>Ingestion:</b>	Rinse mouth. If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
<b>Inhalation:</b>	Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
<b>Skin Contact:</b>	Wipe off paste with paper towel or cloth. Wash exposed area with soap and water. Seek medical attention if irritation persists..
<b>Eye Contact:</b>	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

## **IX. SHIPPING INFORMATION**

### **Canadian Transportation of Dangerous Goods**

<b>Proper Shipping Name:</b>	Not regulated
<b>Hazard Class:</b>	None
<b>UN/ID No:</b>	None

### **IATA**

<b>Proper Shipping Name:</b>	Not regulated
<b>Class or Division:</b>	None
<b>UN/ID Number:</b>	None

### **IMDG**

<b>Proper Shipping:</b>	Not regulated
<b>Hazard Class:</b>	None
<b>UN Number:</b>	None

## **X. PREPARATION INFORMATION**

**Estimated HMIS Classification:** HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0  
HMIS is a registered trademark of the National Paint and Coatings Assn.

**Estimated NFPA Rating:** HEALTH 1, FLAMMABILITY 1, REACTIVITY 0  
NFPA is a registered trademark of the National Fire Protection Assn.

**Product Name: PC ATF RESISTANT RTV GASKET  
MAKER 85 GR**

**Item No: 31870**

**X. PREPARATION INFORMATION**

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety

**Revision Date:** February 28, 2011

**Company:**

Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

**Revision Number:** 5

**Telephone No.:** 1-87-Permatex (877) 376-2839