

Permatex Canada, Inc.
8450 Lawson Road, Unit 1
Milton, ON Canada L9T 0A4
Telephone: 1-87-Permatex
(877) 376-2839
Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: PC NO TOUCH WET N PROTECT 425 GR
Item No: 36081
Product Type: Aerosol cleaner

II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
ACETONE 67-64-1	40-70	5800 mg/kg	not available	500 ppm
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT 64742-47-8	10-30	>5 g/kg	>5.2 mg/L/4H	
CARBON DIOXIDE 124-38-9	7-13	not available	not available	5000 ppm
NAPHTHA (PETROLEUM), LIGHT ALKYLATE 64741-66-8	1-10	>7000 mg/kg	>5.04 mg/L/4H	
2,2,4-TRIMETHYLPENTANE 540-84-1	0.5-1.5	>2500 mg/kg	34.7 mg/L (4H)	

III. PHYSICAL DATA

Physical State/Appearance: Clear liquid
Odour & Odour Threshold: Solvent odour
Specific Gravity: 0.85
Evaporation Rate: >1.0 (butyl acetate = 1)
Vapour Pressure: Not determined
Vapour Density: Heavier than air
Freezing Point: Not determined
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: >38°C (100°F)

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Hazardous Combustion Products: Oxides of carbon
Sensitivity to Static Discharge: Aerosol cans are under pressure and may explode in fire.
Conditions of Flammability: Contents under pressure. Containers may explode if heated. Keep containers cool. Use equipment or shielding to protect personnel from bursting containers.
Flash Point/Range: Flame projection >15 cm but <100 cm
Autoignition Temperature: Not determined
Upper Explosive Limit: Not determined
Lower Explosive Limit: Not determined

V. REACTIVITY DATA

Conditions Causing Chemical Instability: Stable under normal conditions of use
Materials to avoid: Strong oxidizers, Acids, Alkalies, Reducing agents
Conditions of Reactivity: Avoid excessive heat, sparks and open flame.
Hazardous Decomposition Products: Carbon oxides

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation
Toxicity Information: (See Effects of Acute Exposure to Product)

VI. HAZARDS IDENTIFICATION

Effects of Acute Exposure:	May cause eye, skin and respiratory irritation. May cause nausea, vomiting, pain and stomach upset (i.e., diarrhea).
Effects of Chronic Exposure:	Aspiration can be a hazard if this material is swallowed.
Irritancy of Product:	Eyes: Exposure to liquid or vapor causes mild eye irritation. Symptoms may include burning, tearing, redness, stinging, blurred vision and corneal injury. Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, cracking and skin burns. Preexisting skin disorders may be aggravated by exposure to this material. . Headache, nausea, dizziness, light headedness, staggering gait, giddiness.
Sensitization to Product:	(See Effects of Acute Exposure to Product)
Carcinogenicity:	(See Effects of Chronic Exposure to Product)
Reproductive Toxicity:	(See Effects of Chronic Exposure to Product)
Teratogenicity:	(See Effects of Chronic Exposure to Product)
Mutagenicity:	(See Effects of Chronic Exposure to Product)
Toxicologically Synergistic Products:	None known
WHMIS Hazard Class:	A COMPRESSED GAS, B5 FLAMMABLE AEROSOLS, D2B TOXIC MATERIALS

VII. PREVENTATIVE MEASURES

Personal Protection	
Eyes:	Safety glasses
Skin:	Neoprene or nitrile gloves recommended.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator..
Engineering Controls:	
Spill Procedures:	Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Spills may cause slippery floors.
Protection of Man and Environment:	Follow Canadian and local regulations for disposal.
Handling Procedures and Equipment:	Contents under pressure. Do not puncture or incinerate container. Store away from heat, sparks and open flame. Store at temperatures below 50°C. Avoid breathing vapours.
Special Handling Information:	Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use. Do not spray into eyes or onto skin. This product may cause surfaces to become slippery.

VIII. FIRST AID MEASURES

Ingestion:	Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Get medical attention/advice if you feel unwell.
Skin Contact:	Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

Proper Shipping Name:	Aerosols (May qualify as a Consumer Commodity or Limited Quantity. Refer to TDG Regulations)
Hazard Class:	Class 2.1
UN/ID No:	UN 1950

IATA

Proper Shipping Name:	Consumer Commodity (Not more than 1 liter)
Class or Division:	Class 9
UN/ID Number:	ID 8000

IMDG

Proper Shipping:	Aerosols, Limited Quantity
Hazard Class:	Class 2.1
UN Number:	UN 1950

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 4, PHYSICAL HAZARD 0
HMIS is a registered trademark of the National Paint and Coatings Assn.

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 4, REACTIVITY 0
NFPA is a registered trademark of the National Fire Protection Assn.

**Product Name: PC NO TOUCH WET N PROTECT 425
GR**

Item No: 36081

X. PREPARATION INFORMATION

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: July 15, 2011

Company:
Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

Revision Number: 4

Telephone No.: 1-87-Permatex (877) 376-2839