

Permatex Canada, Inc.  
8450 Lawson Road, Unit 1  
Milton, ON Canada L9T 0A4  
Telephone: 1-87-Permatex  
(877) 376-2839  
Urgence: 800-255-3924 (ChemTel)

## Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

### I. PRODUCT IDENTIFICATION

**Product Name:** SURFACE INSENSITIVE INSTANT ADHESIVE 20 GR.  
**Item No:** 40140  
**Product Type:** Cyanoacrylate ester

### II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
ETHYL-2-CYANOACRYLATE 7085-85-0	>80	>5 mL/kg	not available	0.2 ppm
POLY (METHYL METHACRYLATE) 9011-14-7	<10	not available	not available	
HYDROQUINONE 123-31-9	0.1-1.0	320 mg/kg	not available	1 mg/m <sup>3</sup>

### III. PHYSICAL DATA

**Physical State/Appearance:** Clear liquid  
**Odour & Odour Threshold:** Sharp, irritating  
**Specific Gravity:** 1.06  
**Evaporation Rate:** Not determined  
**Vapour Pressure:** <0.2 mm Hg @ 20°C  
**Vapour Density:** Approximately 3  
**Freezing Point:** Not determined  
**pH:** Does not apply  
**Octanol/Water Coefficient:** Not determined  
**Boiling Point:** >150°C/302°F

### IV. FIRE AND EXPLOSIVE DATA

**Recommended Extinguishing Media:** Carbon dioxide, Dry chemical, Foam  
**Hazardous Combustion Products:** Oxides of carbon  
**Sensitivity to Static Discharge:** Sensitivity to static discharge is expected; material has a flash point below 93°C.  
**Conditions of Flammability:** None anticipated.  
**Flash Point/Range:** Greater than 65 degrees C Method: TCC  
**Autoignition Temperature:** Not determined  
**Upper Explosive Limit:** Not determined  
**Lower Explosive Limit:** Not determined

### V. REACTIVITY DATA

**Conditions Causing Chemical Instability:** None  
**Materials to avoid:** Polymerized by contact with water, alcohols, amines, alkalis  
**Conditions of Reactivity:** Hazardous polymerization may occur if over-catalyzed or insufficiently aerated after catalyzation. This polymerization is exothermic..  
**Hazardous Decomposition Products:** Carbon oxides

### VI. HAZARDS IDENTIFICATION

**Primary Routes of Exposure:** Eye and skin contact, ingestion, inhalation  
**Toxicity Information:** (See Effects of Acute Exposure to Product)  
**Effects of Chronic Exposure:** None known.  
**Irritancy of Product:** Vapor is irritating to eyes and mucous membrane above TLV. Prolonged and repeated overexposure to vapors may produce symptoms of non-allergic asthma in sensitive individuals.  
**Sensitization to Product:** (See Effects of Acute Exposure to Product)  
**Carcinogenicity:** (See Effects of Chronic Exposure to Product)  
**Reproductive Toxicity:** (See Effects of Chronic Exposure to Product)  
**Teratogenicity:** (See Effects of Chronic Exposure to Product)

## **VI. HAZARDS IDENTIFICATION**

**Mutagenicity:** (See Effects of Chronic Exposure to Product)  
**Toxicologically Synergistic Products:** None known  
**WHMIS Hazard Class:** D2B TOXIC MATERIALS

## **VII. PREVENTATIVE MEASURES**

### **Personal Protection**

**Eyes:** Safety glasses.  
**Skin:** Neoprene or nitrile gloves recommended. Do not wear protective clothes containing cotton.  
**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator.  
**Engineering Controls:** Flood with water to polymerize. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.  
**Spill Procedures:** Follow Canadian and local regulations for disposal.  
**Protection of Man and Environment:** Store in a dry area below 35°C.  
**Handling Procedures and Equipment:** Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use.  
**Special Handling Information:**

## **VIII. FIRST AID MEASURES**

**Ingestion:** Ingestion is not likely. The adhesive solidifies and adheres in the mouth. If lips are accidentally stuck together, apply lots of warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips with direct opposing action. Saliva will lift the adhesive in one half to two days.  
**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.  
**Skin Contact:** Remove excess adhesive. Soak in warm, soapy water. The adhesive will come loose from the skin in several hours. Cured adhesive does not present a health hazard even when bonded to the skin. For skin adhesion, first immerse the bonded surfaces in warm, soapy water. Peel or roll the surfaces apart with the aid of a blunt edge, e.g., spatula or teaspoon handle; then remove adhesive from the skin with soap and water. Do not try to pull surfaces apart with a direct opposing action. Cyanoacrylates give off heat on solidification. In rare cases, a large drop will increase in temperature enough to cause a burn. Burns should be treated normally after the lump of cyanoacrylate is released from the tissue as described above.  
**Eye Contact:** In the event that eyelids are stuck together or bonded to the eyeball, wash thoroughly with warm water and apply a gauze patch. The eye will open without further action, typically in 1-4 days. There will be no residual damage. Do not try to open the eyes by manipulation. If cyanoacrylate is introduced into the eyes, it will attach to the eye protein and will disassociate from it over intermittent periods, generally several hours. This will cause periods of weeping until clearance is achieved. During this period, double vision may be experienced together with a lachrymatory effect, and it is important to understand the cause and realize that disassociation will normally occur within a matter of hours, even with gross contamination.

## **IX. SHIPPING INFORMATION**

### **Canadian Transportation of Dangerous Goods**

**Proper Shipping Name:** Not regulated  
**Hazard Class:** None  
**UN/ID No:** None

### **IATA**

**Proper Shipping Name:** Not regulated  
**Class or Division:** None  
**UN/ID Number:** None

### **IMDG**

**Proper Shipping:** Not regulated  
**Hazard Class:** None  
**UN Number:** None

## **X. PREPARATION INFORMATION**

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 2, PHYSICAL HAZARD 0  
HMIS is a registered trademark of the National Paint and Coatings Assn.

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 2, REACTIVITY 1  
NFPA is a registered trademark of the National Fire Protection Assn.

**Product Name: SURFACE INSENSITIVE INSTANT  
ADHESIVE 20 GR.**

**Item No: 40140**

**X. PREPARATION INFORMATION**

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety

**Revision Date:** June 23, 2011

**Company:**

Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

**Revision Number:** 2

**Telephone No.:** 1-87-Permatex (877) 376-2839