

Permatex Canada, Inc.
 8450 Lawson Road, Unit 1
 Milton, ON Canada L9T 0A4
 Telephone: 1-87-Permatex
 (877) 376-2839
 Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: MAXIMUM TEMPERATURE THREAD SEALANT WITH PTFE 50 ML
Item No: 56750
Product Type: Anaerobic

II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
POLYGLYCOL DIMETHACRYLATE 25852-47-5	20-40	not available	not available	
POLYESTER RESIN MIXTURE	25-35	not available	not available	
POLYETHYLENE GLYCOL ESTER 18268-70-7	10-20	18 g/kg	not available	
POLYETHYLENE HOMOPOLYMER 9002-88-4	<10	not available	12 g/m ³ /30M	
TITANIUM DIOXIDE 13463-67-7	<5	>10000 mg/kg	not available	10 mg/m ³
POLYTETRAFLUOROETHYLENE 9002-84-0	<5	not available	45 mg/m ³ /30M	
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	<5	>5,000 mg/kg	not available	10 mg/m ³
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<2	382 mg/kg	200 ppm/4H	

III. PHYSICAL DATA

Physical State/Appearance: White paste
Odour & Odour Threshold: Mild odour
Specific Gravity: 1.02
Evaporation Rate: Not determined
Vapour Pressure: <5 mmHg @ 21°C
Vapour Density: Heavier than air
Freezing Point: Not determined
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: >150°C

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam
Hazardous Combustion Products: Oxides of carbon, Oxides of nitrogen
Sensitivity to Static Discharge: Sensitivity to static discharge is not expected
Conditions of Flammability: None anticipated.
Flash Point/Range: >95°C COC
Autoignition Temperature: Not determined
Upper Explosive Limit: Not determined
Lower Explosive Limit: Not determined

V. REACTIVITY DATA

Conditions Causing Chemical Instability: Stable
Materials to avoid: Amines, Heavy metal salts, Strong oxidizing agents
Conditions of Reactivity: High temperatures
Hazardous Decomposition Products: Carbon oxides, Oxides of nitrogen

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure:	Eye and skin contact, ingestion, inhalation
Existing Conditions Aggravated by Exposure:	Allergy, eczema, skin conditions
Toxicity Information:	(See Effects of Acute Exposure to Product)
Effects of Acute Exposure:	May cause eye and skin irritation. May cause allergic skin reactions and sensitization.
Effects of Chronic Exposure:	Prolonged or repeated skin contact may cause sensitization, with itching, swelling or rashes on later exposure. Note: This product does not contain microcrystalline silica. See (Effects of Acute Exposure to Product).
Irritancy of Product:	
Sensitization to Product:	(See Effects of Acute Exposure to Product)
Carcinogenicity:	(See Effects of Chronic Exposure to Product)
Reproductive Toxicity:	(See Effects of Chronic Exposure to Product)
Teratogenicity:	(See Effects of Chronic Exposure to Product)
Mutagenicity:	(See Effects of Chronic Exposure to Product)
Toxicologically Synergistic Products:	None known
WHMIS Hazard Class:	D2B TOXIC MATERIALS

VII. PREVENTATIVE MEASURES

Personal Protection	
Eyes:	Safety glasses..
Skin:	Neoprene or nitrile gloves recommended.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator.
Engineering Controls:	In case of insufficient ventilation, wear an organic vapor respirator.
Spill Procedures:	Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.
Protection of Man and Environment:	Follow Canadian and local regulations for disposal.
Handling Procedures and Equipment:	Store in a dry area below 35°C.
Special Handling Information:	Avoid contact with skin and eyes.

VIII. FIRST AID MEASURES

Ingestion:	If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation:	Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact:	Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

Proper Shipping Name:	Not regulated
Hazard Class:	None
UN/ID No:	None

IATA

Proper Shipping Name:	Not regulated
Class or Division:	None
UN/ID Number:	None

IMDG

Proper Shipping:	Not regulated
Hazard Class:	None
UN Number:	None

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0
HMIS is a registered trademark of the National Paint and Coatings Assn.

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1
NFPA is a registered trademark of the National Fire Protection Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

**Product Name: MAXIMUM TEMPERATURE THREAD
SEALANT WITH PTFE 50 ML**

Item No: 56750

X. PREPARATION INFORMATION

Revision Date: January 13, 2011

Company:
Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

Revision Number: 1

Telephone No.: 1-87-Permatex (877) 376-2839