

ITW Permatex Canada
8450 Lawson Road, Unit 1
Milton, ON Canada L9T 0J8
Telephone: (800) 924-6994
Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: PC MAXIMUM TEMPERATURE SLEEVE RETAINER 36 ML
Item No: 62041
Product Type: Anaerobic

II. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | Weight% | LD50/oral/rat | LC50/inhalation/rat | ACGIH; TLV-TWA |
|---|---------|---------------|--------------------------|----------------------|
| ETHOXYLATED BISPHENOL A DIMETHACRYLATE 24448-20-2 | 55-75 | not available | not available | |
| HYDROXYALKYL METHACRYLATE 27813-02-1 | 10-30 | 11200 mg/kg | not available | |
| N,N-M-PHENYLENE DIMALEIMIDE 3006-93-7 | 5-15 | 1370 mg/kg | 55 mg/m ³ /4H | |
| TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7 | <3 | >5,000 mg/kg | not available | 10 mg/m ³ |
| DIMETHYLBENZYL HYDROPEROXIDE 80-15-9 | <3 | 382 mg/kg | 200 ppm/4H | |

III. PHYSICAL DATA

Physical State/Appearance: Green liquid
Odour & Odour Threshold: Mild odour
Specific Gravity: 1.1
Evaporation Rate: Not determined
Vapour Pressure: <5 mmHg @ 21°C
Vapour Density: Not determined
Freezing Point: Not determined
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: >150°C/302°F

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam
Hazardous Combustion Products: Oxides of carbon
Sensitivity to Static Discharge: Sensitivity to static discharge is not expected.
Conditions of Flammability: None anticipated.
Flash Point/Range: >95°C COC
Autoignition Temperature: Not determined
Upper Explosive Limit: Not determined
Lower Explosive Limit: Not determined

V. REACTIVITY DATA

Conditions Causing Chemical Instability: None
Materials to avoid: Strong oxidizing agents, Peroxides, Reducing agents
Conditions of Reactivity: None.
Hazardous Decomposition Products: Carbon oxides

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation
Existing Conditions Aggravated by Exposure: Preexisting eye, skin and respiratory disorders
Toxicity Information: (See Effects of Acute Exposure to Product)

VI. HAZARDS IDENTIFICATION

Effects of Acute Exposure: May cause eye and skin irritation.
Effects of Chronic Exposure: May cause an allergic skin reaction. Note: This product does not contain microcrystalline silica.
Irritancy of Product: Irritation of eyes, skin, nose and throat. May cause dermatitis on prolonged contact in sensitive individuals.
Sensitization to Product: (See Effects of Acute Exposure to Product)
Carcinogenicity: (See Effects of Chronic Exposure to Product)
Reproductive Toxicity: (See Effects of Chronic Exposure to Product)
Teratogenicity: (See Effects of Chronic Exposure to Product)
Mutagenicity: (See Effects of Chronic Exposure to Product)
Toxicologically Synergistic Products: None known
WHMIS Hazard Class: D2B TOXIC MATERIALS

VII. PREVENTATIVE MEASURES

Personal Protection
Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator.
Engineering Controls: In case of insufficient ventilation, wear an organic vapor respirator.
Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.
Protection of Man and Environment: Follow Canadian and local regulations for disposal.
Handling Procedures and Equipment: Store in a dry area below 35°C.
Special Handling Information: Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use.

VIII. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

Proper Shipping Name: Not regulated
Hazard Class: None
UN/ID No: None

IATA (Air)

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG (Vessel)

Proper Shipping Name: Not regulated
Hazard Class: None
UN Number: None

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0
HMIS is a registered trademark of the National Paint and Coatings Association

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0
(NFPA is a registered trademark of the National Fire Protection Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: August 19, 2011

Company:

ITW Permatex Canada. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0J8

Revision Number: 2

Telephone No.: 1-87-Permatex (877) 376-2839