

Permatex Canada, Inc.  
 8450 Lawson Road, Unit 1  
 Milton, ON Canada L9T 0A4  
 Telephone: 1-87-Permatex  
 (877) 376-2839  
 Urgence: 800-255-3924

## Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

### I. PRODUCT IDENTIFICATION

**Product Name:** BEARING MOUNT FOR WORN PARTS 50ML  
**Item No:** 66050  
**Product Type:** Anaerobic

### II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
ETHOXYLATED BISPHENOL A DIMETHACRYLATE 24448-20-2	40-50	not available	not available	
HYDROXYALKYL METHACRYLATE 27813-02-1	30-40	11200 mg/kg	not available	
TREATED SILICON DIOXIDE, SYNTHETIC, CRYSTALLINE-FREE 67762-90-7	<10	>5,000 mg/kg	not available	10 mg/m <sup>3</sup>
POLYESTER RESIN MIXTURE	<10	not available	not available	
POLYVINYL ACETATE 9003-20-7	<3	not available	not available	
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	382 mg/kg	200 ppm/4H	

### III. PHYSICAL DATA

**Physical State/Appearance:** Silver paste  
**Odour & Odour Threshold:** Mild odour  
**Specific Gravity:** 1.1  
**Evaporation Rate:** Not determined  
**Vapour Pressure:** <5 mmHg @ 21°C  
**Vapour Density:** Not determined  
**Freezing Point:** Not determined  
**pH:** Does not apply  
**Octanol/Water Coefficient:** Not determined  
**Boiling Point:** >150°C

### IV. FIRE AND EXPLOSIVE DATA

**Recommended Extinguishing Media:** Carbon dioxide, Dry chemical, Foam  
**Hazardous Combustion Products:** Oxides of carbon  
**Sensitivity to Static Discharge:** Sensitivity to static discharge is not expected.  
**Conditions of Flammability:** None anticipated  
**Flash Point/Range:** >95°C COC  
**Autoignition Temperature:** Not determined  
**Upper Explosive Limit:** Not determined  
**Lower Explosive Limit:** Not determined

### V. REACTIVITY DATA

**Conditions Causing Chemical Instability:** None  
**Materials to avoid:** Reducing agents, Amines, Heat, Heavy metal salts  
**Conditions of Reactivity:** Hazardous polymerization may occur if over-catalyzed or insufficiently aerated after catalyzation. This polymerization is exothermic.  
**Hazardous Decomposition Products:** Carbon dioxide, Carbon monoxide

### VI. HAZARDS IDENTIFICATION

**Primary Routes of Exposure:** Eye and skin contact, ingestion, inhalation

## **VI. HAZARDS IDENTIFICATION**

**Existing Conditions Aggravated by** None known

**Exposure:**

**Toxicity Information:** (See Effects of Acute Exposure to Product)

**Effects of Acute Exposure:** May cause severe eye irritation and moderate skin irritation. Possible inhalation irritant. May be harmful if swallowed. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**Effects of Chronic Exposure:** May cause an allergic skin reaction.

**Irritancy of Product:** May cause dermatitis on prolonged contact in sensitive individuals.

**Sensitization to Product:** (See Effects of Acute Exposure to Product)

**Carcinogenicity:** (See Effects of Chronic Exposure to Product)

**Reproductive Toxicity:** (See Effects of Chronic Exposure to Product)

**Teratogenicity:** (See Effects of Chronic Exposure to Product)

**Mutagenicity:** (See Effects of Chronic Exposure to Product)

**Toxicologically Synergistic Products:** None known

**WHMIS Hazard Class:** D2B TOXIC MATERIALS

## **VII. PREVENTATIVE MEASURES**

**Personal Protection**

**Eyes:** Safety glasses.

**Skin:** Neoprene or nitrile gloves recommended.

**Ventilation:** General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. Wear an organic vapor respirator.

**Engineering Controls:** Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

**Spill Procedures:** Follow Canadian and local regulations for disposal.

**Protection of Man and Environment:** Store in a dry area below 35°C.

**Handling Procedures and Equipment:** Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use.

**Special Handling Information:** Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use.

## **VIII. FIRST AID MEASURES**

**Ingestion:** If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

**Inhalation:** Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

**Skin Contact:** Wash off with soap and water. If skin irritation persists, call a physician.

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

## **IX. SHIPPING INFORMATION**

**Canadian Transportation of Dangerous Goods**

**Proper Shipping Name:** Not Regulated

**Hazard Class:** None

**UN/ID No:** None

**IATA**

**Proper Shipping Name:** Not regulated

**Class or Division:** None

**UN/ID Number:** None

**IMDG**

**Proper Shipping:** Not regulated

**Hazard Class:** None

**UN Number:** None

## **X. PREPARATION INFORMATION**

**Estimated HMIS Classification:** HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

HMIS is a registered trademark of the National Paint and Coatings Assn.

**Estimated NFPA Rating:** HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

NFPA is a registered trademark of the National Fire Protection Assn.

**Prepared By:** Denise Boyd, Manager-Environmental, Health & Safety

**Revision Date:** July 22, 2009

**Product Name: BEARING MOUNT FOR WORN PARTS  
50ML**

**Item No: 66050**

**X. PREPARATION INFORMATION**

**Company:**

Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

**Revision Number: 1**

**Telephone No.: 1-87-Permatex (877) 376-2839**