

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product Name Slick 50 High Mileage Fuel System Treatment
Synonym(s) 710002
CAS # Mixture
Product Use Fuel System Cleaner
Manufacturer ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON L7G 0C6 CA
Phone: 1-905-693-8900
Emergency Telephone: 1-877-504-9352

2. Hazards Identification

Emergency Overview CAUTION
COMBUSTIBLE LIQUID AND VAPOUR.
EYE AND SKIN IRRITANT.

Potential short term health effects

Routes of exposure Eye, Skin contact, Skin absorption, Inhalation, Ingestion.

Eyes May cause irritation.

Skin May cause irritation. May be absorbed through the skin.

ACGIH - Threshold Limit Values - Skin Notations

Kerosene 8008-20-6 Skin - potential significant contribution to overall exposure by the cutaneous route

Inhalation May cause respiratory tract irritation.

Ingestion May cause stomach distress, nausea or vomiting.

Target organs Eyes. Respiratory system. Skin.

Chronic effects Prolonged or repeated exposure can cause drying, defatting and dermatitis.

Signs and symptoms Symptoms may include redness, oedema, drying, defatting and cracking of the skin.
Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Potential environmental effects See section 12.

3. Composition/Information on Ingredients

Ingredient(s)	CAS #	Percent
Solvent naphtha (petroleum), light aromatic	64742-95-6	10 - 30
Kerosene	8008-20-6	30 - 60

4. First Aid Measures

First aid procedures

Eye contact Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.

Skin contact Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.

Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.

Ingestion Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.

General advice Keep away from sources of ignition. No smoking. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting Measures

Flammable properties	Combustible by WHMIS criteria.
Extinguishing media	
Suitable extinguishing media	Dry chemical. Foam. Carbon dioxide.
Unsuitable extinguishing media	Not available
Protection of firefighters	
Specific hazards arising from the chemical	Not available
Protective equipment for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus.
Hazardous combustion products	May include and are not limited to: Oxides of carbon.
Explosion data	
Sensitivity to mechanical impact	Not available
Sensitivity to static discharge	Not available

6. Accidental Release Measures

Personal precautions	Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas.
Methods for containment	Stop leak if you can do so without risk.
Methods for cleaning up	Remove sources of ignition. Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labelled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills in original containers for re-use.

7. Handling and Storage

Handling	Use good industrial hygiene practices in handling this material. Avoid contact with eyes and skin. Wash thoroughly after handling.
Storage	Keep out of reach of children. Do not store at temperatures above 120°F (49°C). Store in a closed container away from incompatible materials. Keep away from heat and flame.

8. Exposure Controls / Personal Protection

Exposure limit values	
Ingredient(s)	Exposure limit values
Kerosene	ACGIH-TLV TWA: 200 mg/m ³ Skin: 100 mg/m ³
Solvent naphtha (petroleum), light aromatic	ACGIH-TLV Not established
Engineering controls	General ventilation normally adequate.
Personal protective equipment	
Eye/Face protection	Wear safety glasses with side shields.
Hand protection	Rubber gloves. Confirm with a reputable supplier first.
Skin and body protection	As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Appearance	Clear
Colour	Amber
Form	Liquid
Odour	Hydrocarbon
Odour threshold	Not available
Physical state	Liquid
pH	Not available
Freezing point	Not available
Boiling point	Not available
Pour point	Not available
Evaporation Rate	Not available
Flash point	55 °C (131.00 °F)
Auto-ignition temperature	> 200 °C (> 392.00 °F)
Flammability limits in air, lower, % by volume	0.6
Flammability Limits in Air, Upper, % by Volume	6
Vapour pressure	Not available
Vapour density	Not available
Specific gravity	0.89 - 0.9
Octanol/water coefficient	Not available
Solubility (H2O)	Negligible

10. Stability and Reactivity

Reactivity	None known.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Heat, open flames, static discharge, sparks and other ignition sources. Do not mix with other chemicals.
Incompatible materials	Acids. Oxidizers.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Component analysis - LC50

Ingredient(s)	LC50
Kerosene	5.2801 mg/m ³ rat
Solvent naphtha (petroleum), light aromatic	5.2 mg/l/4h rat

Component analysis - Oral LD50

Ingredient(s)	LD50
Kerosene	5000 mg/kg rat; 16300 mg/kg guinea pig
Solvent naphtha (petroleum), light aromatic	4700 mg/kg rat

Effects of acute exposure

Eye	May cause irritation.
Skin	May cause irritation. May be absorbed through the skin.

ACGIH - Threshold Limit Values - Skin Notations

Kerosene 8008-20-6 Skin - potential significant contribution to overall exposure by the cutaneous route

Inhalation May cause respiratory tract irritation.

Ingestion May cause stomach distress, nausea or vomiting.

Sensitisation Non-hazardous by WHMIS criteria.

Chronic effects Non-hazardous by WHMIS criteria.

Carcinogenicity	Non-hazardous by WHMIS criteria.
ACGIH - Threshold Limit Values - Carcinogens	
Kerosene	8008-20-6 A3 - Confirmed animal carcinogen with unknown relevance to humans.
Mutagenicity	Non-hazardous by WHMIS criteria.
Reproductive effects	Non-hazardous by WHMIS criteria.
Teratogenicity	Non-hazardous by WHMIS criteria.
Name of Toxicologically Synergistic Products	Not available

12. Ecological Information

Ecotoxicity	Components of this product have been identified as having potential environmental concerns.	
Ecotoxicity - Freshwater Fish - Acute Toxicity Data		
Solvent naphtha (petroleum), light aromatic	64742-95-6	96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L
Ecotoxicity - Water Flea - Acute Toxicity Data		
Solvent naphtha (petroleum), light aromatic	64742-95-6	48 Hr EC50 Daphnia magna: 6.14 mg/L
Persistence and degradability	Not available	
Bioaccumulation/accumulation	Not available	
Mobility in environmental media	Not available	
Environmental effects	Not available	
Aquatic toxicity	Not available	
Partition coefficient	Not available	
Chemical fate information	Not available	
Other adverse effects	Not available	

13. Disposal Considerations

Disposal instructions	Review federal, provincial, and local government requirements prior to disposal.
Waste from residues / unused products	Not available
Contaminated packaging	Not available

14. Transport Information

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

Proper shipping name	FLAMMABLE LIQUID, N.O.S. (Kerosene)
Hazard class	3
UN number	UN1993
Packing group	III
Additional information:	
Special provisions	16
Packaging exceptions	Limited quantity <5L



15. Regulatory Information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.
WHMIS classification	Class B - Division 3 - Combustible Liquid, Class D - Division 2B
WHMIS status	Controlled

WHMIS labeling



Inventory Status


Country(s) or region	Inventory Name	On Inventory (Yes/No)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND HMIS/NFPA	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

Health	/ 1
Flammability	2
Physical Hazard	0
Personal Protection	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

05-Jan-2012

Effective Date

01-Nov-2011

Expiry Date

01-Nov-2014

Prepared by

Dell Tech Laboratories Ltd. (519) 858-5021

Other Information

For an updated MSDS, please contact the supplier/manufacturer listed on the first page of the document.

This MSDS conforms to the ANSI Z400.1/Z129.1-2010 Standard.