

Permatex Canada, Inc.
8450 Lawson Road, Unit 1
Milton, ON Canada L9T 0A4
Telephone: 1-87-Permatex
(877) 376-2839
Urgence: 800-255-3924

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: PC 80BR YELLOW SUPER WEATHERSTRIP ADHESIVE 59ML
Item No: 80539
Product Type: Adhesive

II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
ACETONE 67-64-1	15-25	5800 mg/kg	not available	500 ppm
METHYL ETHYL KETONE (BUTANONE) 78-93-3	15-25	2737 mg/kg	32 g/m ³ /4H	200 ppm
TOLUENE 108-88-3	10-20	636 mg/kg	12.5 mg/L/4H; >26700 ppm/1H	20 ppm
N-HEXANE 110-54-3	10-20	25 g/kg	48000 ppm/4H	50 ppm

III. PHYSICAL DATA

Physical State/Appearance: Yellow paste
Odour & Odour Threshold: Solvent odour
Specific Gravity: 0.89
Evaporation Rate: >1.0 (butyl acetate = 1)
Vapour Pressure: 175 mmHg @ 20°C
Vapour Density: Heavier than air
Freezing Point: Not determined
pH: Does not apply
Octanol/Water Coefficient: Not determined
Boiling Point: 55°C

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Hazardous Combustion Products: Oxides of carbon, Oxides of nitrogen
Sensitivity to Static Discharge: Sensitivity to static discharge is expected; material has a flashpoint less than or equal to 10 degrees C..
Conditions of Flammability: FLAMMABLE: Keep from heat and open flame. Keep containers cool.
Flash Point/Range: -18°C
Autoignition Temperature: Not determined
Upper Explosive Limit: 13.0%
Lower Explosive Limit: 1.2%

V. REACTIVITY DATA

Conditions Causing Chemical Instability: None
Materials to avoid: Strong oxidizers, Strong bases, Acids
Conditions of Reactivity: Avoid excessive heat, sparks and open flame
Hazardous Decomposition Products: Carbon oxides, Oxides of nitrogen

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation
Existing Conditions Aggravated by Exposure: Toluene: Eye, liver, skin, respiratory and central nervous system diseases; alcoholism. Methyl ethyl ketone: Eye, skin and respiratory diseases..
Toxicity Information: (See Effects of Acute Exposure to Product)

VI. HAZARDS IDENTIFICATION

Effects of Acute Exposure:

Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation and/or a feeling like that of fine dust in the eyes. Prolonged and repeated exposure may dry the skin. Symptoms may include redness, burning, drying and cracking. Preexisting skin disorders may be aggravated by exposure. Skin absorption is possible, but harmful effects are not expected under normal conditions of use. Overexposure by inhalation may cause nasal and respiratory irritation, central nervous system affects, dizziness, drowsiness, weakness, fatigue, nausea, headache and possible unconsciousness. Intentionally concentrating and inhaling the vapor may be harmful or fatal.

Effects of Chronic Exposure:

Reports have associated repeated and prolonged overexposure to solvents with permanent brain damage and nervous system damage. This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals. Repeated exposure to Toluene has been associated with high frequency hearing loss based on animal studies. Overexposure to methyl ethyl ketone and n-hexane may cause peripheral nerve damage (that of arms and legs) and result in muscular weakness and loss of sensation.

Irritancy of Product:

Skin: Exposure may cause mild skin irritation. Prolonged or repeated exposure may dry the skin. Symptoms may include redness, burning, drying, cracking and skin burns. Preexisting skin disorders may be aggravated by exposure to this material. Skin absorption is possible, but harmful effects are not expected from this route of exposure under normal conditions of handling and use. Breathing: Symptoms are typically seen at air concentrations exceeding the recommended exposure limits. Symptoms of exposure may include: 1) Nasal and respiratory irritation (nose, throat and lung), preexisting lung disorder, e.g. asthma-like conditions, may be aggravated by exposure to this material. 2) Central nervous system (CNS) depression effects; dizziness, drowsiness, weakness, fatigue, nausea, headache, possible unconsciousness, coma and even death. 3) Cardiac arrhythmias (irregular heartbeat). 4) Cough. Swallowing: This material can enter the lungs during swallowing or vomiting and cause lung inflammation and/or damage. Aspiration of material into the lungs can cause chemical pneumonia which can be fatal. Symptoms may include: 1) throat irritation, 2) gastrointestinal irritation (nausea, vomiting, diarrhea), 3) central nervous system depression; dizziness, drowsiness, weakness, fatigue, nausea, headache, possible unconsciousness, coma and even death, 4) high blood sugar. Eyes: Exposure to liquid or vapor causes mild eye irritation. Symptoms may include burning, tearing, redness, stinging, blurred vision and corneal injury.

Sensitization to Product:

(See Effects of Acute Exposure to Product)

Carcinogenicity:

(See Effects of Chronic Exposure to Product)

Reproductive Toxicity:

(See Effects of Chronic Exposure to Product)

Teratogenicity:

(See Effects of Chronic Exposure to Product)

Mutagenicity:

(See Effects of Chronic Exposure to Product)

Toxicologically Synergistic Products: None known

WHMIS Hazard Class:

B2 FLAMMABLE LIQUIDS, D2B TOXIC MATERIALS, D2A VERY TOXIC MATERIALS

VII. PREVENTATIVE MEASURES

Personal Protection

Eyes:

Safety glasses.

Skin:

Neoprene or nitrile gloves recommended.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product. In case of insufficient ventilation, wear an organic vapor respirator.

Engineering Controls:

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Prevent from entering waterways or sewers.

Protection of Man and Environment:

Follow Canadian and local regulations for disposal.

Handling Procedures and Equipment:

Flammable. Store away from heat, sparks and open flame. Store at temperatures below 50°C. Use with adequate ventilation. Avoid breathing vapours. Use good personal hygiene. Avoid smoking, eating or drinking during use. Wash with soap and water after handling.

Special Handling Information:

Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use. Keep away from heat, sparks and open flame. Do not spray into eyes or onto skin.

VIII. FIRST AID MEASURES

Ingestion:

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation:

Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact:

Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

Eye Contact:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

Product Name: PC 80BR YELLOW SUPER
WEATHERSTRIP ADHESIVE 59ML

Item No: 80539

IX. SHIPPING INFORMATION

Proper Shipping Name: Adhesives (May qualify as a Consumer Commodity or Limited Quantity. Refer to TDG).
Hazard Class: Class 3; Packing Group II
UN/ID No: UN 1133

IATA

Proper Shipping Name: Consumer Commodity (Not more than 500 ml)
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG

Proper Shipping: Adhesives containing flammable liquid, Limited Quantity
Hazard Class: Class 3, PG II
UN Number: UN 1133

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0
HMIS is a registered trademark of the National Paint and Coatings Assn.

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0
NFPA is a registered trademark of the National Fire Protection Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: October 26, 2009

Company:
Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

Revision Number: 3

Telephone No.: 1-87-Permatex (877) 376-2839