

Permatex Canada, Inc.
 8450 Lawson Road, Unit 1
 Milton, ON Canada L9T 0A4
 Telephone: 1-87-Permatex
 (877) 376-2839
 Urgence: 800-255-3924 (ChemTel)

Canadian Workplace Hazardous Materials Information System Material Safety Data Sheet

I. PRODUCT IDENTIFICATION

Product Name: PC 120DA BELT DRESSING & CONDITIONER 369GR AE
Item No: 80552
Product Type: Aerosol coating

II. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	LD50/oral/rat	LC50/inhalation/rat	ACGIH; TLV-TWA
WATER 7732-18-5	>50	not available	not available	
N-HEXANE 110-54-3	<10	25 g/kg	48000 ppm/4H	50 ppm
PETROLEUM GASES, LIQUEFIED, SWEETENED 68476-86-8	<10	not available	not available	
POLYBUTYLENE RESIN 9003-29-6	<10	>34600 mg/kg	4820 mg/m ³ /4h	

III. PHYSICAL DATA

Physical State/Appearance: White liquid/Aerosol
Odour & Odour Threshold: Sweet
Specific Gravity: 0.9-1.0
Evaporation Rate: <1 (butyl acetate = 1)
Vapour Pressure: Not determined
Vapour Density: Heavier than air
Freezing Point: Not determined
pH: Not determined
Octanol/Water Coefficient: Not determined
Boiling Point: >95°C

IV. FIRE AND EXPLOSIVE DATA

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Hazardous Combustion Products: Carbon dioxide
Sensitivity to Static Discharge: Aerosol cans are under pressure and may explode in fire.
Conditions of Flammability: Contents under pressure. Keep containers cool. Containers may explode if heated. Use equipment or shielding to protect personnel from bursting containers.
Flash Point/Range: No flame projection
Autoignition Temperature: Not determined
Upper Explosive Limit: Not determined
Lower Explosive Limit: Not determined

V. REACTIVITY DATA

Conditions Causing Chemical Instability: None
Materials to avoid: Strong oxidizers
Conditions of Reactivity: Avoid excessive heat, sparks and open flame
Hazardous Decomposition Products: Carbon oxides

VI. HAZARDS IDENTIFICATION

Primary Routes of Exposure: Eye and skin contact, ingestion, inhalation
Existing Conditions Aggravated by Exposure: None known
Toxicity Information: (See Effects of Acute Exposure to Product)
Effects of Acute Exposure: May cause eye, skin and respiratory irritation. High concentration may cause respiratory irritation and central nervous system depression with dizziness, headache, unconsciousness.

VI. HAZARDS IDENTIFICATION

Effects of Chronic Exposure: Overexposure to methyl ethyl ketone and n-hexane may cause peripheral nerve damage (that of arms and legs) and result in muscular weakness and loss of sensation.
Vapor above TLV is irritating to eyes, nose, and throat and can cause headache, dizziness, nausea.

Irritancy of Product: Vapor above TLV is irritating to eyes, nose, and throat and can cause headache, dizziness, nausea.

Sensitization to Product: (See Effects of Acute Exposure to Product)

Carcinogenicity: (See Effects of Chronic Exposure to Product)

Reproductive Toxicity: (See Effects of Chronic Exposure to Product)

Teratogenicity: (See Effects of Chronic Exposure to Product)

Mutagenicity: (See Effects of Chronic Exposure to Product)

Toxicologically Synergistic Products: None known

WHMIS Hazard Class: A COMPRESSED GAS, D2B TOXIC MATERIALS

VII. PREVENTATIVE MEASURES

Personal Protection

Eyes: Safety glasses.

Skin: Neoprene or nitrile gloves recommended.

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Engineering Controls: In case of insufficient ventilation, wear an organic vapor respirator.

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

Protection of Man and Environment: Follow Canadian and local regulations for disposal.

Handling Procedures and Equipment: Contents under pressure. Do not puncture or incinerate container. Store away from heat, sparks and open flame. Store at temperatures below 50°C.

Special Handling Information: Avoid prolonged breathing of vapor. Keep away from eyes. Avoid prolonged contact with skin. Do not smoke while using. Wash hands after use. Keep away from heat, sparks and open flame. Do not spray into eyes or onto skin.

VIII. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.

Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

IX. SHIPPING INFORMATION

Canadian Transportation of Dangerous Goods

Proper Shipping Name: Aerosols (May qualify as a Consumer Commodity or Limited Quantity. Refer to TDG Regulations)

Hazard Class: Class 2.2

UN/ID No: UN 1950

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)

Class or Division: Class 9

UN/ID Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity

Hazard Class: Class 2.2

UN Number: UN 1950

X. PREPARATION INFORMATION

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0
HMIS is a registered trademark of the National Paint and Coatings Assn.

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0
NFPA is a registered trademark of the National Fire Protection Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety

Revision Date: October 27, 2010

Company:
Permatex Canada, Inc. 8450 Lawson Rd. Unit 1, Milton, ON L9T 0A4

**Product Name: PC 120DA BELT DRESSING &
CONDITIONER 369GR AE**

Item No: 80552

X. PREPARATION INFORMATION

Revision Number: 2

Telephone No.: 1-87-Permatex (877) 376-2839