

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product Name Slick 50 Engine Treatment
Synonym(s) P-401
CAS # Mixture
Product Use Fuel System Cleaner
Manufacturer ITW Permatex Canada
35 Brownridge Road, Unit 1
Halton Hills, ON L7G 0C6 CA
Phone: 1-905-693-8900
Emergency Telephone: 1-877-504-9352

2. Hazards Identification

Emergency Overview Contact may cause eye and skin irritation.
Potential short term health effects
Routes of exposure Eye, Skin contact, Inhalation, Ingestion.
Eyes May cause irritation.
Skin May cause irritation.
Inhalation May cause respiratory tract irritation.
Ingestion May cause stomach distress, nausea or vomiting.
Target organs Eyes. Skin.
Chronic effects Repeated or prolonged skin exposure may cause acne/folliculitis.
Signs and symptoms Symptoms may include redness, oedema, drying, defatting and cracking of the skin. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Potential environmental effects See section 12.

3. Composition/Information on Ingredients

Ingredient(s)	CAS #	Percent
Distillates (petroleum), solvent-dewaxed heavy paraffin	64742-65-0	60 - 100

4. First Aid Measures

First aid procedures
Eye contact Flush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical attention if irritation persists.
Skin contact Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Inhalation If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Ingestion Do not induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention.
Notes to physician Symptoms may be delayed.
General advice If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire-fighting Measures

Flammable properties Not flammable by WHMIS criteria.

Extinguishing media

Suitable extinguishing media Dry chemical. Foam. Carbon dioxide. Fog.

Unsuitable extinguishing media Not available

Protection of firefighters

Specific hazards arising from the chemical Not available

Protective equipment for firefighters Firefighters should wear full protective clothing including self contained breathing apparatus.

Hazardous combustion products May include and are not limited to: Oxides of carbon.

Explosion data

Sensitivity to mechanical impact Not available

Sensitivity to static discharge Not available

6. Accidental Release Measures

Personal precautions

Keep unnecessary personnel away. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep people away from and upwind of spill/leak.

Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods for containment

Stop leak if you can do so without risk.

Methods for cleaning up

Before attempting clean up, refer to hazard data given above. Small spills may be absorbed with non-reactive absorbent and placed in suitable, covered, labelled containers. Prevent large spills from entering sewers or waterways. Contact emergency services and supplier for advice. Never return spills in original containers for re-use.

7. Handling and Storage

Handling

Use good industrial hygiene practices in handling this material.
Avoid contact with eyes and skin.
Avoid breathing vapours or mists of this product.
Wash thoroughly after handling.

Storage

Keep out of reach of children. Store in a closed container away from incompatible materials.

8. Exposure Controls / Personal Protection

Exposure limit values

Ingredient(s)

Exposure limit values

Distillates (petroleum), solvent-dewaxed heavy paraffin

ACGIH-TLV

Not established

Engineering controls

General ventilation normally adequate.

Personal protective equipment

Eye/Face protection

Wear safety glasses with side shields.

Hand protection

Rubber gloves. Confirm with a reputable supplier first.

Skin and body protection

As required by employer code.

Respiratory protection

Where exposure guideline levels may be exceeded, use an approved NIOSH respirator.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

9. Physical and Chemical Properties

Appearance

Oily

Colour

Amber / Brown

Form

Liquid

Odour

Odourless

Odour threshold

Not available

Physical state

Liquid

pH	Not available
Freezing point	Not available
Boiling point	> 280 °C (> 536.00 °F) (estimated)
Pour point	Not available
Evaporation Rate	Not available
Flash point	221.1 °C (429.98 °F)
Auto-ignition temperature	> 320 °C (> 608.00 °F)
Flammability limits in air, lower, % by volume	1 (typical)
Flammability Limits in Air, Upper, % by Volume	10 (typical)
Vapour pressure	< 0.5 kPa @20°C (estimated)
Vapour density	Not available
Specific gravity	Not available
Octanol/water coefficient	> 6 (based on similar products)
Solubility (H2O)	Negligible

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	Hazardous polymerisation does not occur.
Chemical stability	Stable under recommended storage conditions.
Conditions to avoid	Heat, open flames, static discharge, sparks and other ignition sources. Do not mix with other chemicals.
Incompatible materials	Oxidizers.
Hazardous decomposition products	May include and are not limited to: Oxides of carbon.

11. Toxicological Information

Component analysis - LC50

Ingredient(s)	LC50
Distillates (petroleum), solvent-dewaxed heavy paraffin	2.18 mg/l/4h rat

Component analysis - Oral LD50

Ingredient(s)	LD50
Distillates (petroleum), solvent-dewaxed heavy paraffin	5000 mg/kg rat

Effects of acute exposure

Eye	May cause irritation.
Skin	May cause irritation.
Inhalation	May cause respiratory tract irritation.
Ingestion	May cause stomach distress, nausea or vomiting.
Sensitisation	Non-hazardous by WHMIS criteria.
Chronic effects	Non-hazardous by WHMIS criteria.
Carcinogenicity	Non-hazardous by WHMIS criteria.
Mutagenicity	Non-hazardous by WHMIS criteria.
Reproductive effects	Non-hazardous by WHMIS criteria.
Teratogenicity	Non-hazardous by WHMIS criteria.
Name of Toxicologically Synergistic Products	Not available

12. Ecological Information

Ecotoxicity	See below	
Ecotoxicity - Freshwater Fish - Acute Toxicity Data		
Distillates (petroleum), solvent-dewaxed heavy paraffin	64742-65-0	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Ecotoxicity - Water Flea - Acute Toxicity Data		
Distillates (petroleum), solvent-dewaxed heavy paraffin	64742-65-0	48 Hr EC50 Daphnia magna: >1000 mg/L
Persistence and degradability	Not available	
Bioaccumulation/accumulation	Not available	
Mobility in environmental media	Not available	
Environmental effects	Not available	
Aquatic toxicity	Not available	
Partition coefficient	> 6 (based on similar products)	
Chemical fate information	Not available	
Other adverse effects	Not available	

13. Disposal Considerations

Disposal instructions	Review federal, provincial, and local government requirements prior to disposal.
Waste from residues / unused products	Not available
Contaminated packaging	Not available

14. Transport Information

Transportation of Dangerous Goods (TDG - Canada)
Not regulated as dangerous goods.


15. Regulatory Information

Canadian federal regulations	This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.	
WHMIS status	Not Controlled	
Inventory Status		
Country(s) or region	Inventory Name	On Inventory (Yes/No)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)		

16. Other Information

LEGEND HMIS/NFPA	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

Health	/ 1
Flammability	1
Physical Hazard	0
Personal Protection	X



Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 20-Jan-2012
Effective Date 01-Nov-2011
Expiry Date 01-Nov-2014
Prepared by Dell Tech Laboratories Ltd. (519) 858-5021
Other Information For an updated MSDS, please contact the supplier/manufacturer listed on the first page of the document.

This MSDS conforms to the ANSI Z400.1/Z129.1-2010 Standard.