Material Safety Data Sheet





1. Product and company identification

Product name : Air Mixture
Synonym : Not available.
Trade name : Air Mixture
Material uses : Many.

Manufacturer : Praxair Canada Inc. 1 City Centre Drive

Suite 1200

Mississauga, ON L5B 1M2

MSDS # : E-6778-H

Validation date : October 15, 2013.

Print date : October 15, 2013.

In case of emergency : Emergencies: * 1-800-363-0042

*Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair

sales representative.

Product type : Gas.

2. Hazards identification

Physical state : Gas.

Odor : Odourless

Emergency overview : CAUTION!

High pressure gas. May be fatal if inhaled. May cause dizziness and drowsiness.

Self-contained breathing apparatus may be required by rescue workers.

Contains gas under pressure. In a fire or if heated, a pressure increase will occur and the container may burst or explode. Do not puncture or incinerate container. Avoid

breathing gas. Use only with adequate ventilation.

Routes of entry : Inhalation

Potential acute health effects

Inhalation: May cause mild irritation, and dizziness.

Ingestion : As this product is a gas, refer to the inhalation section.

SkinContact with rapidly expanding gas may cause burns or frostbite.EyesContact with rapidly expanding gas may cause burns or frostbite.

Potential chronic health effects

Chronic effects
 No known significant effects or critical hazards.
 Carcinogenicity
 No known significant effects or critical hazards.
 Mutagenicity
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.
 Target organs
 No known significant effects or critical hazards

Over-exposure signs/symptoms

Inhalation: No specific data.Ingestion: No specific data.Skin: No specific data.Eyes: No specific data.

Medical conditions : None.

aggravated by over-

exposure 10/15/2013.

E-6778-H Copy

2. Hazards identification

See toxicological information (section 11)

3. Composition/information on ingredients

<u>Canada</u>		
<u>Name</u>	CAS number	<u>%</u>
air	132259-10-0	95 - 99.999
AND CONTAINS ONE OR MORE OF THE FOLLOWING GASES:		
Methane	74-82-8	0 - 5
deuterium	7782-39-0	0 - 4.9
hydrogen	1333-74-0	0 - 4
ethane	74-84-0	0 - 2.9
ethylene	74-85-1	0 - 2.7
propane	74-98-6	0 - 2.1
propylene	115-07-1	0 - 2
butane	106-97-8	0 - 1.8
1-Butene	106-98-9	0 - 1.8
isobutane	75-28-5	0 - 1.8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

Eye contact	: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
Skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
Inhalation	: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	: As this product is a gas, refer to the inhalation section.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed.

5. Fire-fighting measures

Flammability of the product	1	Contains gas under pressure) .	In a fire or if heated,	a pres	sure	increase	will oc	cur a	and
		the container may burst or ex	φl	lode.						

Extinguishing media

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

: None known.

nitrogen oxides

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Contact supplier immediately for specialist advice. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

The exposed person may need to be kept under medical surveillance for 48 hours.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

C - Air Mixture (E-6778-H)

Fire-fighting measures 5.

Special remarks on fire

hazards

: Not available.

Special remarks on explosion hazards

: Not available.

Accidental release measures 6.

Personal precautions

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing gas. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

Environmental precautions

Ensure emergency procedures to deal with accidental gas releases are in place to avoid contamination of the environment. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill

: Immediately contact emergency personnel. Stop leak if without risk.

Large spill

: Immediately contact emergency personnel. Stop leak if without risk. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Handling and storage 7.

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Contains gas under pressure. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Empty containers retain product residue and can be hazardous. Do not puncture or incinerate container.

Storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in a dry, cool and well-ventilated area, away from incompatible materials (see section 10). Keep container tightly closed and sealed until ready for use.

8. **Exposure controls/personal protection**

Occupational exposure limits		TWA (TWA (8 hours) STEL (15		(15 mins)		Ceilin	g			
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
1-Butene	US ACGIH 1/2009	250	-	_	-	-	-	-	-	-	
	BC 10/2009	250	-	-	-	-	-	-	-	-	
propylene	US ACGIH 1/2009	500	-	-	-	-	-	-	-	-	
	AB 4/2009	500	860	-	-	-	-	-	-	-	
	BC 10/2009	500	-	-	-	-	-	-	-	-	
	ON 8/2008	500	-	-	-	-	-	-	-	-	
propane	US ACGIH 1/2009	1000	-	-	-	-	-	-	-	-	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 10/2009	1000	-	-	-	-	-	-	-	-	
	ON 8/2008	1000	-	-	-	-	-	-	-	-	
	QC 6/2008	1000	1800	-	-	-	-	-	-	-	
Methane	US ACGIH 1/2009	1000	-	-	-	-	-	-	-	-	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 10/2009	1000	-	-	-	-	-	-	-	-	
	ON 8/2008	1000	-	-	-	-	-	-	-	-	
hydrogen	Simple asphyxiant.										[2]
ethylene	US ACGIH 1/2009	200	-	-	-	-	-	-	-	-	[-
•	AB 4/2009	200	229	-	-	-	-	-	-	-	
	BC 10/2009	200	-	-	-	-	-	-	-	-	
	ON 8/2008	200	-	-	-	-	-	-	-	-	
ethane	US ACGIH 1/2009	1000	-	-	-	-	-	-	-	-	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 10/2009	1000	-	L	-	-	-	-	-	-	
	ON 8/2008	1000	-	L	-	-	-	-	-	-	
butane	US ACGIH 1/2009	1000	-	-	-	-	-	-	-	}	
	AB 4/2009	1000	-	-	-	-	-	-	-	}	
	BC 10/2009	600	-	-	750	-	-	-	-	-	

10/15/2013.

E-6778-H

Copyright © 2009, Praxair Canada Inc.

C-A	ir Mix	cture (l	E-67	78-H)
-----	--------	----------	------	-------

8. Exposure controls/personal protection

	ON 8/2008	800	1900	-	-	-	-	-	-	_	
	QC 6/2008	800	1900	-	-	-	-	-	-	-	
isobutane	US ACGIH 1/2009	1000	-	-	-	-	-	-	-	_	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 10/2009	1000	-	-	-	-	-	-	-	-	
	ON 8/2008	800	1900	-	-	-	-	-	-	-	

[2]Oxygen Depletion [Asphyxiant]

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Select in accordance with provincial regulations, local bylaws or guidelines. Selection should be based on the current CSA standard Z94.4, "Selection, Care, and Use of Respirators." Respirators should also be approved by NIOSH and MSHA.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Other protection

: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or quidelines.

9. Physical and chemical properties

Physical state

: Gas.

Flash point

: Not applicable.

Burning time

Not applicable.

Burning rate

Not applicable.

Auto-ignition temperature

: Not applicable.

Flammable limits

: Not available.

Color Odor Colourless.

10/15/2013.

: Odourless E-6778-H

Copyright © 2009, Praxair Canada Inc.

9. Physical and chemical properties

Taste : Not available.

Molecular weight : Not applicable. Molecular formula : Not applicable. pН Not available. **Boiling/condensation point** : Not available. **Melting/freezing point** : Not available. **Critical temperature** : Not available. **Relative density** : Not available. Vapor pressure Not available. : Not available. Vapor density

Volatility : 100%

Odor threshold : Not available.

Evaporation rate : Not available.

Viscosity : Not available.

Ionicity (in water) : Not available.

Dispersibility properties : Not available.

Solubility : Not available.

Physical/chemical : Not available.

properties comments

COEFFICIENT OF WATER/OIL

DISTRIBUTION:

: Not applicable.

10. Stability and reactivity

Chemical stability : The product is stable.

Conditions to avoid : No specific data.

Materials to avoid : No specific data.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient nameResultSpeciesDoseExposurebutaneLC50 InhalationRat658 g/m34 hoursVapor

isobutane LC50 Inhalation Rat 658000 mg/m3 4 hours

Vapor

LC50 Inhalation Rat 57 pph 15 minutes

Gas.

Not available.

Conclusion/Summary

Chronic toxicity

Product/ingredient name Result Species Dose Exposure

Not available.

Conclusion/Summary: Not available.

Irritation/Corrosion

Product/ingredient name Result Species Score Exposure Observation

Not available.

Sensitizer

C - Air Mixture (E-6778-H)

11. Toxicological information

Product/ingredient name Route of Species Result

exposure

Not available.

Conclusion/Summary: Not available.

Carcinogenicity

Product/ingredient name Result Species Dose Exposure

Not available.

Conclusion/Summary: Not available.

Classification

Product/ingredient name ACGIH IARC EPA NIOSH NTP OSHA

Mutagenicity

Product/ingredient name Test Experiment Result

Not available.

Conclusion/Summary: Not available.

Teratogenicity

Product/ingredient name Result Species Dose Exposure

Not available.

Conclusion/Summary: Not available.

Reproductive toxicity

Product/ingredient name Maternal Fertility Development Species Dose Exposure

toxicity toxin

Not available.

Conclusion/Summary : Not available.

Synergistic products : Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name Test Result Species Exposure

Not available.

Conclusion/Summary: Not available.

Persistence/degradability

Product/ingredient name Test Result Dose Inoculum

Not available.

Conclusion/Summary : Not available.

Octanol/water partition : Not available.

coefficient

Bioconcentration factor : Not available.

Mobility : Not available.

Toxicity of the products of

biodegradation

: Not available.

Other adverse effects : No known significant effects or critical hazards.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Do not puncture or incinerate container. Empty pressure vessels should be returned to the supplier.

Waste stream : Not available.

RCRA classification : Not available.

Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
TDG Classification	1956	Compressed gas, n.o.s.	2.2	-		- PRODUCT REPORTALBE QUANTITY (PRQ): Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more.

PG*: Packing group

SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

15. Regulatory information

United States inventory (TSCA 8b)

; All components are listed or exempted.

WHMIS (Canada)

: CLASS A: Compressed gas.

This product is on the DSL list

Canadian lists

: **CEPA Toxic substances**: The following components are listed: Methane; Volatile organic compounds

Canadian ARET: None of the components are listed.

Canadian NPRI: The following components are listed: Propylene; Propane; Volatile

organic compounds; Ethylene; Volatile organic compounds

Alberta Designated Substances: None of the components are listed. **Ontario Designated Substances**: None of the components are listed. **Quebec Designated Substances**: None of the components are listed.

Canada inventory

: All components are listed or exempted.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations

International lists

: Australia inventory (AICS): Not determined.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: Not determined. Korea inventory: Not determined.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): Not determined.

C - Air Mixture (E-6778-H)

Regulatory information 15.

Chemical Weapons

Convention List Schedule I

Chemicals

Chemical Weapons

Convention List Schedule

: Not listed

Not listed

II Chemicals

Chemical Weapons Convention List Schedule

III Chemicals

Not listed

16. Other information

Label requirements

: High pressure gas. May be fatal if inhaled. May cause dizziness and drowsiness. Selfcontained breathing apparatus may be required by rescue workers.

Hazardous Material Information System (U.S.A.)



*An Asterisk used in conjuction whith HMIS health hazards ratings designates a carcinogenic or reproductive hazard.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

References : AV-1 Safe Handling and Storage of Compressed Gas

P-1 Safe Handling of Compressed Gases in Containers

V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections

V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial

Gas Mixtures

Handbook of Compressed Gases, Fifth Edition

Other special

considerations

: Not available.

Date of printing : 10/15/2013 **Date of issue** : 10/15/2013

Date of previous issue : No previous validation.

Version : 0.07

Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: CGA-590 PIN-INDEXED YOKE: Not applicable. **ULTRA-HIGH-**Not applicable.

INTEGRITY **CONNECTION:**

16. Other information

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

For more in-depth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety nformation, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

Praxair and the Flowing Airstream design are trademarks of Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.

Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2

