

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Air/Sulphur Dioxide Mixture	Trade Name: Air/Sulphur Dioxide Mixture
Product Use: Many.	
Chemical Name: Air/Sulphur Dioxide Mixture	Synonym: Not applicable.
Chemical Formula: Not available.	Chemical Family: Not applicable.
Telephone: Emergencies: * 1-800-363-0042	Supplier /Manufacture: Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2 Phone: 905-803-1600 Fax: 905-803-1682

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD ₅₀ (Species & Routes)	LC ₅₀ (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Sulfur dioxide	0.0001-0.9999%	7446-09-5	Not applicable.	1260 ppm	0.25 ppm STEL
Air	99.0001-99.9999%	32259-10-0	Not applicable.	Not applicable.	None

3. Hazards Identification

Emergency Overview

CAUTION! High pressure gas. May be harmful if inhaled. May cause dizziness and drowsiness. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE: Inhalation.

THRESHOLD LIMIT VALUE: TLV-TWA Data from 2010 Guide to Occupational Exposure Values (ACGIH). TLV-TWAs should be used as a guide in the control of health hazards and not as fine lines between safe and dangerous concentrations.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION: NOTE: This product contains traces of Sulfur Dioxide which causes irritation to the eyes, nose and throat.

SKIN CONTACT: NOTE: This product contains traces of Sulfur Dioxide which causes irritation to the eyes, nose and throat.

SKIN ABSORPTION: NOTE: This product contains traces of Sulfur Dioxide which causes irritation to the eyes, nose and throat.

SWALLOWING:

Product Name: Air/Sulphur Dioxide
Mixture

MSDS# E-6803-I

Date: Oct. 15, 2013

NOTE: This product contains traces of Sulfur Dioxide which causes irritation to the eyes, nose and throat.

EYE CONTACT:

NOTE: This product contains traces of Sulfur Dioxide which causes irritation to the eyes, nose and throat.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:

None.

OTHER EFFECTS OF OVEREXPOSURE:

None.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

None.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

None currently known.

CARCINOGENICITY:

Classified 2B (Possible for human.) by IARC [Sulfur dioxide]. Classified A4 (Not classifiable for human or animal.) by ACGIH [Sulfur dioxide].

4. First Aid Measures

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

SKIN CONTACT:

In case of an emergency, give artificial respiration or flush affected areas with water for 15 minutes. Call a physician.

SWALLOWING:

In case of an emergency, give artificial respiration or flush affected areas with water for 15 minutes. Call a physician.

EYE CONTACT:

In case of an emergency, give artificial respiration or flush affected areas with water for 15 minutes. Call a physician.

NOTES TO PHYSICIAN:

None.

5. Fire Fighting Measures

FLAMMABLE : No. **IF YES, UNDER WHAT CONDITIONS?** Not applicable.

FLASH POINT (test method) Not applicable. **AUTOIGNITION TEMPERATURE** Not applicable.

FLAMMABLE LIMITS IN AIR, % by volume: **LOWER:** Not applicable. **UPPER:** Not applicable.

EXTINGUISHING MEDIA:

Oxidizing agent. May accelerate combustion. Use media appropriate for surrounding fire.

SPECIAL FIRE FIGHTING PROCEDURES:

CAUTION! Evacuate all personnel from danger area. Immediately cool container with water spray from maximum distance until cool then move containers away from fire area if without risk. Shut off leak if without risk

UNUSUAL FIRE AND EXPLOSION HAZARD:

Oxidizing agent, may accelerate combustion. Contact with flammable materials may cause fire or explosion. Container may rupture due to heat of fire. No part of a container should be subjected to a temperature higher than 52 C. Most containers are provided with a pressure relief device designed to vent contents when they are exposed to elevated temperatures.

HAZARDOUS COMBUSTION PRODUCTS:

None.

SENSITIVITY TO IMPACT:

Avoid impact against container.

SENSITIVITY TO STATIC DISCHARGE:

Not available.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CAUTION! Shut off leak if without risk.

WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

PRECAUTIONS TO BE TAKEN IN HANDLING:

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to Section 16 for the address and phone number along with a list of other available publications.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

High pressure gas. Use piping and equipment adequately designed to withstand pressures to be encountered. **May be harmful if inhaled.** Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in an environmentally safe manner in compliance with all federal, provincial, and local laws, then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST: Not applicable.

MECHANICAL (general): Adequate.

SPECIAL: Not applicable.

OTHER: Not applicable.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Not required.

SKIN PROTECTION: Preferred for cylinder handling.

EYE PROTECTION: Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

9. Physical and Chemical Properties

PHYSICAL STATE: Gas.	FREEZING POINT: Not available.	pH: Not available.
BOILING POINT: Not available.	VAPOUR PRESSURE: Not applicable.	MOLECULAR WEIGHT: Not applicable.
SPECIFIC GRAVITY: LIQUID (Water = 1) Not available.	SOLUBILITY IN WATER: Not applicable.	
SPECIFIC GRAVITY: VAPOUR (air = 1) Not available.	EVAPORATION RATE (Butyl Acetate=1): Not available.	COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable.
VAPOUR DENSITY: Not available.	% VOLATILES BY VOLUME: Not available.	ODOUR THRESHOLD: Not available.

APPEARANCE & ODOUR: Colourless gas at normal temperature and pressure. Unknown.

10. Stability and Reactivity

STABILITY:	The product is stable.
CONDITIONS OF CHEMICAL INSTABILITY:	See Section 7.
INCOMPATIBILITY (materials to avoid):	Flammable and combustible materials.
HAZARDOUS DECOMPOSITION PRODUCTS:	None.
HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS OF REACTIVITY:	None currently known.

11. Toxicological Information

See section 3.

12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

14. Transport Information

TDG/IMO SHIPPING NAME: Compressed Gas, n.o.s. (Air)

HAZARD CLASS:	IDENTIFICATION #:	PRODUCT REPORTABLE QUANTITY (PRQ):
CLASS 2.2: Non-flammable, and non-toxic gas.	UN1956	Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more

SHIPPING LABEL(s): Non-flammable, non-toxic gas

PLACARD (when required): Non-flammable, non-toxic gas

SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list
WHMIS (Canada) CLASS A: Compressed gas.

International Regulations

EINECS Not available.
DSCL (EEC) R20- Harmful by inhalation.
R40- Possible risks of irreversible effects.

International Lists No products were found.

16. Other Information

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

HAZARD RATING SYSTEM:

HMIS RATINGS:

HEALTH 0

FLAMMABILITY 0

PHYSICAL HAZARD 2

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED:	CGA-660
PIN-INDEXED YOKE:	Not available.
ULTRA-HIGH-INTEGRITY CONNECTION:	Not available.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

AV-1	Safe Handling and Storage of Compressed Gas
P-1	Safe Handling of Compressed Gases in Containers
V-1	Compressed Gas Cylinder Valve Inlet and Outlet Connections
V-7	Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
---	Handbook of Compressed Gases, Fifth Edition

For more indepth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

PREPARATION INFORMATION:

DATE:	October 15, 2013
DEPARTMENT:	Safety and Environmental Services
TELEPHONE:	905-803-1600

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

Product Name: Air/Sulphur Dioxide
Mixture

MSDS# E-6803-I

Date: Oct. 15, 2013

Praxair and the *Flowing Airstream* design are trademarks of
Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.
1 City Centre Drive
Suite 1200
Mississauga, ON L5B 1M2

Copyright © 2004, Praxair Canada Inc.

Page 7 of 7