

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Carbon monoxide mixture, non-toxic	Trade Name: Carbon monoxide mixture, non-toxic
Product Use: Not available.	
Chemical Name: Not applicable.	Synonym: Not applicable.
Chemical Formula: Not available.	Chemical Family: Not applicable.
Telephone: Emergencies: * 1-800-363-0042	Supplier /Manufacture: Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2 Phone: 905-803-1600 Fax: 905-803-1682

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD ₅₀ (Species & Routes)	LC ₅₀ (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Carbon monoxide	0.0001-0.99	630-08-0	Not available.	1807 ppm	25 ppm
AND CONTAINS ONE OR MORE OF THE FOLLOWING GASES:					
Butane	0-1.79	106-97-8	Not available.	Not available.	1000 ppm
1-Butene	0-1.79	106-98-9	Not available.	Not available.	250 ppm
Deuterium	0 - 4.89	7782-39-0	Not available.	Not available.	Not available.
Ethane	0 - 2.89	74-84-0	Not available.	Not available.	1000 ppm
Ethylene	0 - 2.69	74-85-1	Not available.	Not available.	200 ppm
Hydrogen	0 - 3.99	1333-74-0	Not available.	Not available.	Simple asphyxiant.
Isobutane	0-1.79	75-28-5	Not available.	Not available.	1000 ppm
Methane	0 - 4.99	74-82-8	Not available.	Not available.	1000 ppm
Propane	0 - 2.09	74-98-6	Not available.	Not available.	1000 ppm
Propylene	0-1.99	115-07-1	Not available.	Not available.	500 ppm
AND CONTAINS ONE OR MORE OF THE FOLLOWING GASES:					
Argon	75 - 99.9998	7440-37-1	Not	Not	Simple asphyxiant.

Product Name: Carbon monoxide
mixture, non-toxic

MSDS# E-6809-G

Date: Oct. 15, 2010

Helium	75 - 99.9998	7440-59-7	available. Not available.	available. Not available.	Simple asphyxiant.
Krypton	75 - 99.9998	7439-90-9	Not available. available.	Not available. available.	Not available.
Neon	72 - 99.9998	7440-01-9	Not available. available.	Not available. available.	Simple asphyxiant.
Nitrogen	72 - 99.9998	7727-37-9	Not available. available.	Not available. available.	Simple asphyxiant.
Xenon	75 - 99.9998	7440-63-3	Not available.	Not available.	Not available.

3. Hazards Identification

Emergency Overview

WARNING! High-pressure gas. Can cause rapid suffocation. May cause dizziness and drowsiness. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE: Inhalation.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION: Asphyxiant. Effects are due to lack of oxygen. Moderate concentrations may cause headaches, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Lack of oxygen can kill.

SKIN CONTACT: No harm expected from vapour.

SKIN ABSORPTION: No evidence of adverse effects from available information.

SWALLOWING: This product is a gas at normal temperature and pressure.

EYE CONTACT: No harm expected from vapour.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:

Not available.

OTHER EFFECTS OF OVEREXPOSURE:

None known.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

The toxicology and the physical and chemical properties of this product suggest that overexposure is unlikely to aggravate medical condition.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

None currently known.

CARCINOGENICITY:

Not listed as carcinogen by OSHA, NTP or IARC.

4. First Aid Measures

INHALATION:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SKIN CONTACT:

This product is a gas at normal temperature and pressure.

SWALLOWING:

This product is a gas at normal temperature and pressure.

EYE CONTACT:

This product is a gas at normal temperature and pressure.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.

5. Fire Fighting Measures

FLAMMABLE : No. **IF YES, UNDER WHAT CONDITIONS?** Non-flammable.

FLASH POINT (test method) Not applicable.

AUTOIGNITION TEMPERATURE Not applicable.

FLAMMABLE LIMITS IN AIR, % by volume:

LOWER: Not applicable.

UPPER: Not applicable.

EXTINGUISHING MEDIA:

This mixture cannot catch fire. Use media appropriate for surrounding fire.

SPECIAL FIRE FIGHTING PROCEDURES:

WARNING Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool; then move them away from fire area if without risk. Self-contained breathing apparatus may be required by rescue workers. If containers are leaking, reduce vapours with water spray or fog. Shut off leak if without risk. Move containers away from fire area if without risk.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Nonflammable material. This material cannot catch fire. Container may rupture due to heat of fire. No part of a container should be subjected to temperature higher than 52 C. Most containers are provided with a pressure relief device designed to vent contents when they are exposed to elevated temperature. Toxic fumes may be produced when heated.

HAZARDOUS COMBUSTION PRODUCTS:

None known.

SENSITIVITY TO IMPACT:

Avoid impact against container.

SENSITIVITY TO STATIC DISCHARGE:

Not applicable.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

WARNING! High-pressure gas. Evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Shut off flow if you can do so without risk. Ventilate area or move cylinder to a well-ventilated area. Test for sufficient oxygen, especially in confined spaces, before allowing reentry.

WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Separate flammable cylinders from oxygen, chlorine, and other oxidizers by at least 6.1 m or use a barricade of non-combustible material. This barricade should be at least 1.53 m high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post “No Smoking or Open Flames” signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 125°F(52°C). Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods. For full details and requirements, see NFPA 50A, published by the National Fire Protection Association.

PRECAUTIONS TO BE TAKEN IN HANDLING:

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions, see section 16.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to section 16 for the address and phone number along with a list of other available publications.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

High pressure gas. Use piping and equipment adequately designed to withstand pressures to be encountered. **Gas can cause rapid suffocation due to oxygen deficiency.** Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **When returning cylinder to supplier,** be sure valve is closed, then install valve outlet plug tightly. **Never work on pressurized system.** If there is a leak, close the cylinder valve. Vent the system down in a safe and environmentally sound manner in compliance with all federal, provincial, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST: Preferred.

MECHANICAL (general): Acceptable.

SPECIAL: Not applicable.

OTHER: Not applicable.

PERSONAL PROTECTION:

Product Name: Carbon monoxide mixture, non-toxic

MSDS# E-6809-H

Date: Oct. 15, 2013

RESPIRATORY PROTECTION: For concentrations up to 10 times the applicable exposure limit any NIOSH/MSHA approved supplied air respirator is recommended. Up to 50 times the TLV, a NIOSH/MSHA approved respirator with a full-face piece or self-contained breathing apparatus is recommended. For higher concentration us only self-contained breathing apparatus operated in the pressure demand mode.. Selection should also be based on the current CSA standard Z94.4, "Selection, Care and Use of Respirators". Respirators should also be approved by NIOSH and MSHA.

SKIN PROTECTION: Wear work gloves when handling cylinders.

EYE PROTECTION: Wear safety glasses when handling cylinders.

Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

9. Physical and Chemical Properties

PHYSICAL STATE: Gas.	FREEZING POINT: Not available - mixture not tested.	pH: Not available.
BOILING POINT Not applicable.	VAPOUR PRESSURE Gas	MOLECULAR WEIGHT: Not available.
SPECIFIC GRAVITY: LIQUID (Water = 1) Not available - mixture not tested.	SOLUBILITY IN WATER,	
SPECIFIC GRAVITY: VAPOUR (air = 1) Not available - mixture not tested.	EVAPORATION RATE (Butyl Acetate=1): Not applicable.	COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable.
VAPOUR DENSITY: Not available - mixture not tested.	% VOLATILES BY VOLUME: Not available.	ODOUR THRESHOLD: Not available.
APPEARANCE & ODOUR: Colourless. Odourless gas		

10. Stability and Reactivity

STABILITY:	The product is stable.
CONDITIONS OF CHEMICAL INSTABILITY:	Not available.
INCOMPATIBILITY (materials to avoid):	Not available - mixture not tested.
HAZARDOUS DECOMPOSITION PRODUCTS:	Not available - mixture not tested.
HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS OF REACTIVITY:	None.

11. Toxicological Information

See section 3.

12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

14. Transport Information

TDG/IMO SHIPPING NAME: Compressed gases n.o.s. (name of major inert component).

HAZARD CLASS:	IDENTIFICATION #:	PRODUCT REPORTABLE QUANTITY (PRQ):
Class 2.2: Non- flammable, non-corrosive and non-toxic gas.	UN1956	Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more

SHIPPING LABEL(s): Non-flammable, non-corrosive and non-toxic gas

PLACARD (when required): Non-flammable, non-corrosive and non-toxic gas

SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list
WHMIS (Canada) CLASS A: Compressed gas.

International Regulations

EINECS Not available.
DSCL (EEC) This product is not classified according to the EU regulations.
International Lists No products were found.

Product Name: Carbon monoxide
mixture, non-toxic

MSDS# E-6809-H

Date: Oct. 15, 2013

16. Other Information

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

HAZARD RATING SYSTEM:

HMIS RATINGS:

HEALTH 0

FLAMMABILITY 0

PHYSICAL HAZARD 2

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED:	CGA-350
PIN-INDEXED YOKE:	Not applicable.
ULTRA-HIGH-INTEGRITY CONNECTION:	Not available.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

AV-1	Safe Handling and Storage of Compressed Gas
P-1	Safe Handling of Compressed Gases in Containers
P-14	Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmosphere
SB-2	Oxygen-Deficient Atmospheres
V-1	Compressed Gas Cylinder Valve Inlet and Outlet Connections
V-7	Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
---	Handbook of Compressed Gases, Fifth Edition

For more indepth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

PREPARATION INFORMATION:

DATE:	October 15, 2013
DEPARTMENT:	Safety and Environmental Services
TELEPHONE:	905-803-1600

Product Name: Carbon monoxide
mixture, non-toxic

MSDS# E-6809-H

Date: Oct. 15, 2013

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

Praxair and the *Flowing Airstream* design are trademarks of
Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.
1 City Centre Drive
Suite 1200
Mississauga, ON L5B 1M2

Copyright © 2004, Praxair Canada Inc.

Page 8 of 8