

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification


Product Name: Carbon Monoxide/Oxygen Mixture Toxic, Flammable	Trade Name: Carbon Monoxide/Oxygen Mixture Toxic, Flammable
Product Use: Many.	
Chemical Name: Carbon Monoxide/Oxygen Mixture Toxic, Flammable	Synonym: Not available.
Chemical Formula: Not available.	Chemical Family: Not applicable.
Telephone: Emergencies: * 1-800-363-0042	Supplier /Manufacture: Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2 Phone: 905-803-1600 Fax: 905-803-1682

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*


2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD ₅₀ (Species & Routes)	LC ₅₀ (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Carbon monoxide	98.5-99.9999	630-08-0	Not applicable.	1807 ppm	25 ppm
Oxygen	0.0001-1.5	7782-44-7	Not applicable.	Not applicable.	None

3. Hazards Identification



Emergency Overview



DANGER! Toxic, flammable, high-pressure gas. May be fatal if inhaled. Symptoms may be delayed. May form explosive mixture with air. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE: Inhalation.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION:

Product Name: Carbon Monoxide/Oxygen
Mixture Toxic, Flammable

MSDS# E-6238-H

Date: Oct. 15, 2013

Depending on the concentrations and the duration of exposure, may cause headache, drowsiness, dizziness, excitation, rapid breathing, excess salivation, nausea, vomiting, hallucinations, confusion, convulsions and unconsciousness. With well established poisoning, the mucosal surface will be bright red (cherry red) in colour. Lack of oxygen can cause death.

SKIN CONTACT: No evidence of adverse effects from available information.

SKIN ABSORPTION: No evidence of adverse effects from available information.

SWALLOWING: A highly unlikely route of exposure.

EYE CONTACT: No evidence of adverse effects from available information.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:

Not available.

OTHER EFFECTS OF OVEREXPOSURE:

Other effects of exposure to CO include embryo toxicity, impaired cardiovascular function, pulmonary edema, pneumatic, gross neuropsychiatric damage, memory impairment, permanent CNS damage and cerebral edema with irreversible brain damage.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Due to the hypoxia from carboxyhemoglobin formation, may aggravate established coronary and cerebral circulatory insufficiency.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

None currently known.

CARCINOGENICITY:

Not listed as carcinogen by OSHA, NTP or IARC.

4. First Aid Measures

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

SKIN CONTACT:

Wash with soap and water.

SWALLOWING:

This product is a gas at normal temperature and pressure.

EYE CONTACT:

Flush with water.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition. With severe cases, the use of hyperbaric oxygen may be beneficial.

5. Fire Fighting Measures

FLAMMABLE : Yes.	IF YES, UNDER WHAT CONDITIONS?	Forms explosive mixtures with air and oxidizing agents. Keep away from flames, heat, and sparks.
FLASH POINT (test method) Flammable gas.	AUTOIGNITION TEMPERATURE	Not available.

Product Name: Carbon Monoxide/Oxygen
Mixture Toxic, Flammable

MSDS# E-6238-H

Date: Oct. 15, 2013

**FLAMMABLE LIMITS
IN AIR, % by volume:**

LOWER: 12.5% (CO)

UPPER: 74% (CO)

EXTINGUISHING MEDIA:

CO₂, dry chemical, water spray or fog.

SPECIAL FIRE FIGHTING PROCEDURES:

DANGER! Evacuate all personnel from danger area. Immediately cool containers with water spray from maximum distance taking care not to extinguish flames. Remove ignition source if without risk. If flames are accidentally extinguished, explosive re-ignition may occur. Use self-contained breathing apparatus. Stop flow of gas if without risk while continuing cooling water spray. Remove all containers from area if without risk. Allow fire to burn out.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Flammable, toxic gas. Cannot be detected by odour. Forms explosive mixtures with air and oxidizing agents. Container may rupture due to heat or fire. Do not extinguish flames due to possibility of explosive re-ignition. Flammable and toxic vapours may spread from spill.

Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with approved device. No part of a container should be subjected to temperature higher than 52 C. Most containers are provided with a pressure relief devices to vent contents when they are exposed to elevated temperature.

HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide.

SENSITIVITY TO IMPACT:

Avoid impact against container.

SENSITIVITY TO STATIC DISCHARGE:

Not available.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

DANGER! DANGER: May explosive mixtures with air (See section seven). Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus when needed. Remove all sources of ignition if without risk. Reduce gas with fog or fine water spray. Shut off leak if without risk. Ventilate area of leak or move leaking container to well ventilated area. Flammable toxic gas may spread from spill. Before entering area, especially confined areas, check atmosphere with appropriate device.

WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

PRECAUTIONS TO BE TAKEN IN HANDLING:

Product Name: Carbon Monoxide/Oxygen
Mixture Toxic, Flammable

MSDS# E-6238-H

Date: Oct. 15, 2013

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to Section 16 for the address and phone number along with a list of other available publications.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

Toxic, flammable high-pressure gas. May be fatal if inhaled. Do not breathe gas. Use piping and equipment adequately designed to withstand pressures to be encountered. **May form explosive mixtures with air.** Keep away from heat, open flame and sparks. Ground all equipment. Use only spark-proof tools and explosion-proof equipment. Store and use with adequate ventilation at all times. Use only in a closed system. Close valve after each use; keep closed even when empty. **When returning cylinder to supplier, be sure valve is closed, then install valve outlet plug tightly. Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in an environmentally safe manner in compliance with all federal, provincial, and local laws, then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST: Explosion-proof system is acceptable.

MECHANICAL (general): Inadequate.

SPECIAL: Use only in a closed system.

OTHER: See SPECIAL.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Select in accordance with provincial regulations, local bylaws or guidelines. Selection should also be based on the current CSA standard Z94.4, "Selection, Care and Use of Respirators". Respirators should also be approved by NIOSH and MSHA.

SKIN PROTECTION: Preferred for cylinder handling.

EYE PROTECTION: Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

9. Physical and Chemical Properties

Product Name: Carbon Monoxide/Oxygen
Mixture Toxic, Flammable

MSDS# E-6238-H

Date: Oct. 15, 2013

PHYSICAL STATE: Gas.	FREEZING POINT: Not available.	pH: Not available.
BOILING POINT: Not available.	VAPOUR PRESSURE: Not available.	MOLECULAR WEIGHT: Not available.
SPECIFIC GRAVITY: Not available. LIQUID (Water = 1)	SOLUBILITY IN WATER: Not available.	
SPECIFIC GRAVITY: Not available. VAPOUR (air = 1)	EVAPORATION RATE (Butyl Acetate=1): Not available.	COEFFICIENT OF WATER/OIL DISTRIBUTION: Not available.
VAPOUR DENSITY: Not available.	% VOLATILES BY VOLUME: Not available.	ODOUR THRESHOLD: Not available.

APPEARANCE & ODOUR: Colourless gas at normal temperature and pressure. Odourless.

10. Stability and Reactivity

STABILITY:	The product is stable.
CONDITIONS OF CHEMICAL INSTABILITY:	Temperatures in excess of 430 C. See Section 7.
INCOMPATIBILITY (materials to avoid):	Oxidizing agents, oxygen, flammables, metal oxides, metals in the presence of moisture, and/or sulphur compounds.
HAZARDOUS DECOMPOSITION PRODUCTS:	Carbon monoxide will decompose to form carbon dioxide and carbon above 400 C.
HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS OF REACTIVITY:	None.

11. Toxicological Information

See section 3.

12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

Product Name: Carbon Monoxide/Oxygen
Mixture Toxic, Flammable

MSDS# E-6238-H

Date: Oct. 15, 2013

14. Transport Information

TDG/IMO SHIPPING NAME: Compressed gas, toxic, flammable, n.o.s. (carbon monoxide)

HAZARD CLASS:	IDENTIFICATION #:	PRODUCT REPORTABLE QUANTITY (PRQ):
CLASS 2.3: Toxic gas. CLASS 2.1: Flammable gas.	UN1953	Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more.

SHIPPING LABEL(s): Toxic gas, Flammable gas

PLACARD (when required): Toxic gas,

SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, nonventilated compartment of vehicle can present serious safety hazards.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list

WHMIS (Canada) CLASS A: Compressed gas.
CLASS B-1: Flammable gas.
CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).

International Regulations

EINECS Not available.

DSCL (EEC) R20- Harmful by inhalation.

International Lists No products were found.

16. Other Information

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

HAZARD RATING SYSTEM:

HMS RATINGS:

HEALTH 1

FLAMMABILITY 4

PHYSICAL HAZARD 2

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: CGA-350

Product Name: Carbon Monoxide/Oxygen
Mixture Toxic, Flammable

MSDS# E-6238-H

Date: Oct. 15, 2013

PIN-INDEXED YOKE: Not available.
ULTRA-HIGH-INTEGRITY CONNECTION: Not available.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

AV-1 Safe Handling and Storage of Compressed Gas
P-1 Safe Handling of Compressed Gases in Containers
P-14 Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmospheres
SB-2 Oxygen-Deficient Atmospheres
V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections
V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
--- Handbook of Compressed Gases, Fifth Edition

For more indepth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

PREPARATION INFORMATION:

DATE: October 15, 2013
DEPARTMENT: Safety and Environmental Services
TELEPHONE: 905-803-1600

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety nformation, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

*Praxair and the Flowing Airstream design are trademarks of
Praxair Canada Inc.*

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.
1 City Centre Drive
Suite 1200
Mississauga, ON L5B 1M2