

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Flammable Gas/Carbon Dioxide Mixture	Trade Name: Flammable Gas/Carbon Dioxide Mixture
Product Use: Many.	
Chemical Name: Flammable Gas/Carbon Dioxide Mixture	Synonym: Not applicable.
Chemical Formula: Not applicable.	Chemical Family: Not applicable.
Telephone: Emergencies: * 1-800-363-0042	Supplier /Manufacture: Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2 Phone: 905-803-1600 Fax: 905-803-1682

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD ₅₀ (Species & Routes)	LC ₅₀ (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Carbon dioxide	0.0001-0.0999	124-38-9	Not available.	Not available.	5000 ppm
AND CONTAINS ONE OR MORE OF THE FOLLOWING GASES:					
Butane	99.9001 - 99.999	106-97-8	Not available.	Not available.	1000 ppm
1-Butene	99.9001 - 99.999	106-98-9	Not available.	Not available.	250 ppm
Deuterium	99.9001 - 99.999	7782-39-0	Not available.	Not available.	Not available.
Ethane	99.9001 - 99.999	74-84-0	Not available.	Not available.	1000 ppm
Ethylene	99.9001 - 99.999	74-85-1	Not available.	Not available.	200 ppm
Hydrogen	99.9001 - 99.999	1333-74-0	Not available.	Not available.	Simple asphyxiant.
Isobutane	99.9001 - 99.999	75-28-5	Not available.	Not available.	Not available.
Methane	99.9001 - 99.999	74-82-8	Not available.	Not available.	Simple asphyxiant.
Propane	99.9001 - 99.999	74-98-6	Not available.	Not available.	1000 ppm
Propylene	99.9001 - 99.999	115-07-1	Not available.	Not available.	500 ppm

3. Hazards Identification

Emergency Overview

DANGER! Flammable, high-pressure gas. May form explosive mixture with air. Can cause rapid suffocation. May cause dizziness and drowsiness. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE: Inhalation.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION: May be mildly irritating to mucous membranes. At very high concentration, may act as an asphyxiant and cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Lack of oxygen can cause death.

SKIN CONTACT: This product is a gas.

SKIN ABSORPTION: No evidence of adverse effects from available information.

SWALLOWING: A highly unlikely route of exposure. This product is a gas at room temperature and pressure.

EYE CONTACT: This product is a gas.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:

Due to the presence of low concentrations of Carbon Dioxide, damage to retinal ganglion cells and central nervous system may occur if overexposure was high and prolonged.

OTHER EFFECTS OF OVEREXPOSURE:

None known.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

Repeated or prolonged exposure is not known to aggravate medical condition. None.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

None currently known.

CARCINOGENICITY:

Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Ethylene].
Classified A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC [Propylene].

4. First Aid Measures

INHALATION:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

SKIN CONTACT:

This product is a gas.

SWALLOWING:

This product is a gas at normal temperature and pressure.

EYE CONTACT:

This product is a gas.

NOTES TO PHYSICIAN:

There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.

5. Fire Fighting Measures

FLAMMABLE : Yes. **IF YES, UNDER WHAT CONDITIONS?** See Unusual Fire and Explosion Hazards.

FLASH POINT (test method) Flammable Gas. **AUTOIGNITION TEMPERATURE** Not available.

FLAMMABLE LIMITS IN AIR, % by volume: **LOWER:** See "% (Vol.)" in Sect. II **UPPER:** See "% (Vol.)" in Sect. II

EXTINGUISHING MEDIA:

CO2, dry chemical, water spray or fog.

SPECIAL FIRE FIGHTING PROCEDURES:

DANGER! Evacuate all personnel from danger area. Immediately cool cylinders with water spray from maximum distance taking care not to extinguish flames. Remove ignition source if without risk. If flames are accidentally extinguished. Explosive re-ignition may occur; therefore, appropriate measures should be taken; e.g., total evacuation. Re-approach with extreme caution. Use self-contained breathing apparatus. Stop flow of gas if without risk while continuing cooling water spray. Remove all containers from area if without risk. Allow fire to burn out.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Flammable gas. Forms explosive mixture with air and oxidizing agents. Container may rupture due to heat of fire. Do not extinguish flames due to possibility of explosive re-ignition. Vapours from this product may spread from spill or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharges, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with appropriate device. No part of a container should be subjected to a temperature higher than 52 C.

HAZARDOUS COMBUSTION PRODUCTS:

These products are carbon oxides (CO, CO2).

SENSITIVITY TO IMPACT:

Avoid impact against container.

SENSITIVITY TO STATIC DISCHARGE:

Not available.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

DANGER! Forms explosive mixtures with air. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus operated in the pressure demand mode and appropriate protective clothing. Remove all sources of ignition if without risk. Reduce vapours with fog or fine water spray. Shut off leak if without risk. Ventilate area of leak or move leaking container to well ventilated area. Flammable vapours may spread from spill. Before entering area, especially confined areas, check atmosphere with appropriate device.

WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Separate flammable cylinders from oxygen, chlorine, and other oxidizers by at least 6.1 m or use a barricade of non-combustible material. This barricade should be at least 1.53 m high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods. For full details and requirements, see NFPA 50A, published by the National Fire Protection Association.

PRECAUTIONS TO BE TAKEN IN HANDLING:

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to section 16 for the address and phone number along with a list of other available publications.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

Flammable high-pressure gas. Use only in a closed system. Use piping and equipment adequately designed to withstand pressures and temperatures to be encountered. Use only spark-proof tools and explosion-proof equipment. Keep away from heat, open flame and sparks. **Gas can cause rapid suffocation due to oxygen deficiency.** Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **Never work on a pressurized system.** If there is a leak, close the cylinder valve. Blow the system down in an environmentally safe manner in compliance with all federal, provincial, and local laws, then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST: Explosion-proof system is acceptable.

MECHANICAL (general): Inadequate.

SPECIAL: Not applicable.

OTHER: Not applicable.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Use respirable fume respirator or air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below TLV. Select in accordance with the provincial regulations or guidelines. Selection should also be based on the current CSA standards Z94.4, "Selection, care and use of respirators". Respirators should be approved by NIOSH and MSHA.

SKIN PROTECTION: Preferred for cylinder handling.

EYE PROTECTION: Wear safety glasses when handling cylinders.

Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

9. Physical and Chemical Properties

PHYSICAL STATE: Gas.	FREEZING POINT: Not available.	pH: Not available.
BOILING POINT: Not available.	VAPOUR PRESSURE: Not applicable.	MOLECULAR WEIGHT: Not applicable.
SPECIFIC GRAVITY: LIQUID (Water = 1) : Not available.	SOLUBILITY IN WATER: Partially soluble in cold water.	
SPECIFIC GRAVITY: VAPOUR (air = 1) : Not available.	EVAPORATION RATE (Butyl Acetate=1): Not available.	COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable.
VAPOUR DENSITY: Not available.	% VOLATILES BY VOLUME: Not available.	ODOUR THRESHOLD: Not available.

APPEARANCE & ODOUR: Colourless gas at normal temperature and pressure.

10. Stability and Reactivity

STABILITY:	The product is stable.
CONDITIONS OF CHEMICAL INSTABILITY:	Temperatures in excess of 435 C. See Section 7.
INCOMPATIBILITY (materials to avoid):	Oxidizing agents, and others depending on the ingredients.
HAZARDOUS DECOMPOSITION PRODUCTS:	CO, CO ₂
HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS OF REACTIVITY:	None currently known.

11. Toxicological Information

See section 3.

12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

14. Transport Information

TDG/IMO SHIPPING NAME: Compressed gas, flammable, n.o.s. (name of the major flammable gas component)

HAZARD CLASS:	IDENTIFICATION #:	PRODUCT REPORTABLE QUANTITY (PRO):
CLASS 2.1: Flammable gas.	UN1954	Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more

SHIPPING LABEL(s): Flammable gas

PLACARD (when required): Flammable gas

SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list
WHMIS (Canada) CLASS A: Compressed gas.
CLASS B-1: Flammable gas.

International Regulations

EINECS Not available.
DSCL (EEC) This product is not classified according to the EU regulations.
International Lists No products were found.

16. Other Information

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

HAZARD RATING SYSTEM:

HMIS RATINGS:

HEALTH 0

FLAMMABILITY 4

Product Name: Flammable Gas/Carbon
Dioxide Mixture

MSDS# E-6221-H

Date: Oct. 15, 2013

PHYSICAL HAZARD 2

*An Asterisk used in conjunction with HMIS health hazards ratings designates a carcinogenic or reproductive hazard.

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: Not available.
PIN-INDEXED YOKE: Not available.
ULTRA-HIGH-INTEGRITY CONNECTION: Not available.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

AV-1 Safe Handling and Storage of Compressed Gas
P-1 Safe Handling of Compressed Gases in Containers
V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections
V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
--- Handbook of Compressed Gases, Fifth Edition

For more indepth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

PREPARATION INFORMATION:

DATE: October 15, 2013
DEPARTMENT: Safety and Environmental Services
TELEPHONE: 905-803-1600

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

*Praxair and the Flowing Airstream design are trademarks of
Praxair Canada Inc.*

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.
1 City Centre Drive
Suite 1200
Mississauga, ON L5B 1M2