

Praxair Material Safety Data Sheet

1. Chemical Product and Company Identification

Product Name: Halocarbon 14	Trade Name: Halocarbon 14
Product Use: Many	
Chemical Name: Tetrafluoromethane	Synonym: Carbon Tetrafluoride, R-14,F-14, Perfluoromethane
Chemical Formula: CF ₄	Chemical Family: Fluorocarbons
Telephone: Emergencies: * 1-800-363-0042	Supplier /Manufacture: Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2
	Phone: 905-803-1600
	Fax: 905-803-1682

**Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD ₅₀ (Species & Routes)	LC ₅₀ (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Tetrafluoromethane	100	75-73-0	Not applicable.	Not available.	None.

3. Hazards Identification

Emergency Overview

CAUTION! High-pressure gas. Harmful if inhaled. Can cause rapid suffocation. Liquid can cause frostbite. May cause dizziness and drowsiness. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE:

Inhalation. Swallowing. Skin absorption. Skin contact. Eye contact.

EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

INHALATION: Asphyxiant. Effects are due to lack of oxygen. High concentrations may cause dizziness, nausea, vomiting disorientation, confusion, incoordination, and narcosis. Very high concentrations may cause suffocation. Lack of oxygen can kill.

SKIN CONTACT: A highly unlikely route of exposure. This product is a gas at normal temperature and pressure. Liquid may cause frostbite.

SKIN ABSORPTION: Prolonged or widespread skin contact with the liquid may result in the absorption of harmful amounts of material.

SWALLOWING: An unlikely route of exposure. This product is a gas at room temperature and pressure, but frostbite of the lips and mouth may result from contact with the liquid.

EYE CONTACT: A highly unlikely route of exposure. This product is a gas at room temperature and pressure. Liquid may cause severe corneal injury.

EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:

No evidence of adverse effects from available information.

OTHER EFFECTS OF OVEREXPOSURE:

At very high concentrations may produce cardiac arrhythmia or arrest due to sensitization of the heart to adrenalin and nor-adrenalin. Exposure to fluorocarbon thermal decomposition products may produce flu-like symptoms including chills, fever, weakness, muscular aches, headache, chest discomfort, sore throat, and dry cough. Complete recovery usually occurs within 24 hours after exposure.

MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

Not available - mixture not tested.

CARCINOGENICITY:

Not listed as carcinogen by OSHA, NTP or IARC.

4. First Aid Measures

INHALATION:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

SKIN CONTACT:

Immediately warm frostbite area with warm water (not to exceed 40 C). In case of massive exposure, remove clothing and shoes while showering with warm water. Get medical attention immediately.

SWALLOWING:

Since the product is a gas and that it is mostly probable that it will be inhaled more than ingested, please consider first to look at the preventive measures in case of inhalation.

EYE CONTACT:

Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. See a physician, preferably an ophthalmologist, immediately.

NOTES TO PHYSICIAN:

Do not administer adrenalin due to the sensitizing effect of fluorocarbons on the myocardium. Treatment of overexposure should be directed at the control of symptoms and the clinical condition.

5. Fire Fighting Measures

FLAMMABLE : No.	IF YES, UNDER WHAT CONDITIONS?	Not applicable.
FLASH POINT (test method) Not applicable.	AUTOIGNITION TEMPERATURE	Not applicable.
FLAMMABLE LIMITS IN AIR, % by volume:	LOWER: Not applicable.	UPPER: Not applicable.

EXTINGUISHING MEDIA:

This material cannot catch fire. Use media appropriate for surrounding fire.

SPECIAL FIRE FIGHTING PROCEDURES:

CAUTION! High-pressure gas. Asphyxiant. Effects are due to lack of oxygen. Evacuate all personnel from danger area. Immediately deluge cylinders with water from maximum distance until cool, then move them away from fire area if without risk. Self-contained breathing apparatus may be required by rescue workers. On-site fire brigades must comply with OSHA 29 CFR 1910.156.

UNUSUAL FIRE AND EXPLOSION HAZARD:

Container may rupture due to heat of fire. No part of a container should be subjected to a temperature higher than 52 C. Most containers are provided with a pressure relief device designed to vent contents when they are exposed to elevated temperature. Toxic fumes may be produced when heated.

HAZARDOUS COMBUSTION PRODUCTS:

At temperatures above 1000 C, carbon dioxide will react with this material to form toxic carbonyl fluoride.

SENSITIVITY TO IMPACT:

Avoid impact against container.

SENSITIVITY TO STATIC DISCHARGE:

Not applicable.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

CAUTION! High-pressure gas. Evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Shut off flow if you can do so without risk. Ventilate area or move cylinder to a well-ventilated area. Test for sufficient oxygen, especially in confined spaces, before allowing reentry.

WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard and product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

7. Handling and Storage

PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Separate flammable cylinders from oxygen, chlorine, and other oxidizers by at least 6.1 m or use a barricade of non-combustible material. This barricade should be at least 1.53 m high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

PRECAUTIONS TO BE TAKEN IN HANDLING:

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions, see Section 16.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to Section 16 for the address and phone number along with a list of other available publications.

OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

High pressure gas. Use piping and equipment adequately designed to withstand pressures to be encountered. **Gas can cause rapid suffocation due to oxygen deficiency.** Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **When returning cylinder to supplier,** be sure valve is closed, then install valve outlet plug tightly. **Never work on pressurized system.** If there is a leak, close the cylinder valve. Vent the system down in a safe and environmentally sound manner in compliance with all federal, provincial, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

8. Exposure Controls/Personal Protection

VENTILATION/ENGINEERING CONTROLS:

LOCAL EXHAUST: Use a local exhaust system, if necessary, to maintain an adequate supply of oxygen in the worker's breathing zone.

MECHANICAL (general): Acceptable.

SPECIAL: None.

OTHER: Not applicable.

PERSONAL PROTECTION:

RESPIRATORY PROTECTION: Use respirable fume respirator or air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below TLV. Select in accordance with the provincial regulations or guidelines. Selection should also be based on the current CSA standards Z94.4, "Selection, care and use of respirators". Respirators should be approved by NIOSH and MSHA.

SKIN PROTECTION: Wear work gloves when handling cylinders.

EYE PROTECTION: Wear safety glasses when handling cylinders.

Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

OTHER PROTECTIVE EQUIPMENT: Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

9. Physical and Chemical Properties

PHYSICAL STATE: Gas.	FREEZING POINT: -184°C (-299.2°F)	pH: Not applicable.
BOILING POINT: -127.9°C (-198.2°F)	VAPOUR PRESSURE: 3161.2 kPa (@ 20°C)	MOLECULAR WEIGHT: 88.01 g/mole
SPECIFIC GRAVITY: 3.038 (Water = 1) LIQUID (Water = 1)	SOLUBILITY IN WATER: Not available.	
SPECIFIC GRAVITY: 3.038 VAPOUR (air = 1)	EVAPORATION RATE (Butyl Acetate=1): Not available.	COEFFICIENT OF WATER/OIL DISTRIBUTION: Not applicable.
VAPOUR DENSITY: 3.65 kg/m³	% VOLATILES BY VOLUME: 100% (v/v).	ODOUR THRESHOLD: Not available.

APPEARANCE & ODOUR: Colourless. Odourless.

10. Stability and Reactivity

STABILITY:	The product is stable.
CONDITIONS OF CHEMICAL INSTABILITY:	None.
INCOMPATIBILITY (materials to avoid):	Aluminum, carbon dioxide (temperatures greater than 1000 C), alloys of more than 2% magnesium in the presence of water.
HAZARDOUS DECOMPOSITION PRODUCTS:	Thermal decomposition may produce toxic fumes of fluorine and carbonyl fluoride.
HAZARDOUS POLYMERIZATION:	Will not occur.
CONDITIONS OF REACTIVITY:	None known.

11. Toxicological Information

See section 3.

12. Ecological Information

WARNING! Contains tetrafluoromethane, a substance which harms public health and environment by destroying ozone in the upper atmosphere. The material is not listed as a marine pollutant by TDG regulations.

13. Disposal Considerations

WASTE DISPOSAL METHOD: Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

14. Transport Information

TDG/IMO SHIPPING NAME: Tetrafluoromethane, Compressed

HAZARD CLASS:	CLASS 2.2: Non-flammable, non-corrosive and non-toxic gas.	IDENTIFICATION #:	UN1982	PRODUCT REPORTABLE QUANTITY (PRQ):	Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more.
----------------------	---	--------------------------	--------	---	--

SHIPPING LABEL(s): Non-flammable, non-corrosive and non-toxic gas

PLACARD (when required): Non-flammable, non-corrosive and non-toxic gas

SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list

WHMIS (Canada) CLASS A: Compressed gas.

International Regulations

EINECS Not available.

DSCL (EEC) This product is not classified according to the EU regulations.

International Lists No products were found.

16. Other Information

MIXTURES:

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

HAZARD RATING SYSTEM:

HMIS RATINGS:

HEALTH 0

FLAMMABILITY 0

PHYSICAL HAZARD 3

STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: CGA-580 CGA-320

PIN-INDEXED YOKE: Not available.

ULTRA-HIGH-INTEGRITY CONNECTION: CGA-716

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

- AV-1 Safe Handling and Storage of Compressed Gas
- P-1 Safe Handling of Compressed Gases in Containers
- P-14 Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmosphere
- SB-2 Oxygen-Deficient Atmospheres
- V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections
- V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
- Handbook of Compressed Gases, Fifth Edition

PREPARATION INFORMATION:

DATE: October 15, 2013

DEPARTMENT: Safety and Environmental Services

TELEPHONE: 905-803-1600

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

Praxair and the *Flowing Airstream* design are trademarks of
Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.
1 City Centre Drive
Suite 1200
Mississauga, ON L5B 1M2