Mixture

# **Praxair Material Safety Data Sheet**

|                                 | 1. Chemical Product a                   | nd Company Ide                              | entification   |
|---------------------------------|---|---|--|
| Product Name: Product Use:      | Inert Gas/Carbon Monoxide Mixture Many. | Trade Name:                                 | Inert Gas/Carbon Monoxide Mixture  |
| Chemical Name: Chemical Formula | Not Applicable.  Not avaliable.         | Synonym:<br>Chemical Family                 | Not avaliable.  y: Not applicable.   |
| Telephone:                      | <b>Emergencies:</b> * 1-800-363-0042    | Supplier<br>/Manufacture:<br>Phone:<br>Fax: | Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2 905-803-1600 905-803-1682 |

<sup>\*</sup>Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.

## 2. Composition and Information on Ingredients

| INGREDIENTS   | % (VOL)           | CAS<br>NUMBER | LD <sub>50</sub> (Species & Routes) | LC <sub>50</sub> (Rat, 4 hrs.) | TLV-TWA<br>(ACGIH) |
|---|-------------------|---------------|-------------------------------------|--------------------------------|--------------------|
| Carbon monoxide  AND CONTAINS ONE OR MORE OF THE FOLLOWING GASES: | 0.0001-0.9999     | 630-08-0      | Not available.                      | 1807 ppm                       | 25 ppm             |
| Argon   | 99.0001- 99.9999  | 7440-37-1     | Not available.                      | Not<br>available.              | Simple asphyxiant. |
| Helium  | 99.0001- 99.9999  | 7440-59-7     | Not available.                      | Not available.                 | Simple asphyxiant. |
| Krypton   | 99.0001- 99.9999  | 7439-90-9     | Not available.                      | Not available.                 | Simple asphyxiant. |
| Neon  | 99.0001 - 99.9999 | 7440-01-9     | Not available.                      | Not available.                 | Simple asphyxiant. |
| Nitrogen  | 99.0001 - 99.9999 | 7727-37-9     | Not available.                      | Not available.                 | Simple asphyxiant. |
| Xenon   | 99.0001 - 99.9999 | 7440-63-3     | Not available.                      | Not available.                 | Simple asphyxiant. |

## 3. Hazards Identification

## **Emergency Overview**

CAUTION! High pressure gas. Vigorously accelerates combustion. Self-contained breathing apparatus may be required by rescue workers.

ROUTES OF EXPOSURE:

Inhalation.

Monoxide Mixture

## **EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:**

**INHALATION:** Asphyxiant. Moderate concentrations may cause headache, drowsiness, dizziness,

excitation, excess salvations, vomiting and unconsciousness.

**SKIN CONTACT:** No evidence of adverse effects from available information.

**SKIN ABSORPTION:** No evidence of adverse effects from available information.

**SWALLOWING:** Unlikely route of exposure. This product is a gas at normal temperature and pressure.

**EYE CONTACT:** No evidence of adverse effects from available information.

## **EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:**

Not available

## **OTHER EFFECTS OF OVEREXPOSURE:**

None currently known. This product is an asphyxiant. Lack of oxygen can cause death.

NOTE: This product contains traces (up to 2.0%) of Carbon Monoxide, which is known to cause central nervous system damage.

#### **MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:**

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

## SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:

None currently known.

#### **CARCINOGENICITY:**

Not listed as carcinogen by OSHA, NTP or IARC.

## 4. First Aid Measures

#### **INHALATION:**

Remove to fresh air. If not breathing, give artifical respiration. If breathing is difficult, qualified personnel may give oxygen. Call a physician.

#### **SKIN CONTACT:**

Wash with soap and water.

#### **SWALLOWING:**

This product is a gas at normal temperature and pressure.

## **EYE CONTACT:**

Flush with water.

#### **NOTES TO PHYSICIAN:**

There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.

Monoxide Mixture

| 5. Fire Fighting Measures                     |           |                        |  |  |  |
|---|-----------|------------------------|--|--|--|
| FLAMMABLE: No. IF YES, UNDER WHAT CONDITIONS? |           | •                      | Not applicable.                          |  |  |
| FLASH POINT (test method)                     | Not appli | cable.                 | AUTOIGNITION Not applicable. TEMPERATURE |  |  |
| FLAMMABLE LII<br>IN AIR, % by vol             |           | LOWER: Not applicable. | UPPER: Not appliable.                    |  |  |

## **EXTINGUISHING MEDIA:**

Gas mixture cannot catch fire. Use media appropriate for surrounding fire.

#### **SPECIAL FIRE FIGHTING PROCEDURES:**

**CAUTION!** Evacuate all personnel to a safe distance. Immediately deluge containers with water spray from maximum distance until cool, them move containers away from fire area if without risk.

#### **UNUSUAL FIRE AND EXPLOSION HAZARD:**

Gas (high pressure gas) cannot catch fire. Container may rutpure due to heat of fire. No part of a container should be subjected to a temperature higher than 52 C. Most containers are provided with a pressure relief device designed to vent contents when they are exposed to elevated temperature.

## **HAZARDOUS COMBUSTION PRODUCTS:**

Not applicable.

#### **SENSITIVITY TO IMPACT:**

Avoid impact against container.

#### **SENSITIVITY TO STATIC DISCHARGE:**

Not avaliable.

#### 6. Accidental Release Measures

#### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**CAUTION!** 

Evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Shut off leak if without risk. Ventilate area of leak or move leaking container to well ventilated area. Test area, especially confined areas, for sufficent oxygen content prior to permitting reentry of personnel.

#### **WASTE DISPOSAL METHOD:**

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

#### 7. Handling and Storage

#### PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

#### PRECAUTIONS TO BE TAKEN IN HANDLING:

Monoxide Mixture

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to section 16 for the address and phone number along with a list of other available publications.

## OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

High pressure gas. Use piping and equipment adequately designed to withstand pressures to be encountered. Gas can cause rapid suffocation due to oxygen deficiency. Store and use with adequate ventilation. Close valve after each use; keep closed even when empty. Prevent reverse flow. Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. Never work on a pressurized system. If there is a leak, close the cylinder valve. Blow the system down in an environmentally safe manner in compliance with all federal, provincial, and local laws, then repair the leak. Never place a compressed gas cylinder where it may become part of an electrical circuit.

| 8. Exposure Controls/Personal Protection | 1 |
|--|---|
|--|---|

**VENTILATION/ENGINEERING CONTROLS:** 

**LOCAL EXHAUST:** Preferred.

MECHANICAL (general): Acceptable.

**SPECIAL:** Not applicable.

**OTHER:** Not applicable.

PERSONAL PROTECTION:

**RESPIRATORY PROTECTION:** Select in accordance with provincial regulations, local bylaws or

guidelines. Selection should also be based on the current CSA standard Z94.4, "Selection, Care and Use of Respirators". Respirators should also be approved by NIOSH and MSHA.

**SKIN PROTECTION:** Preferred for cylinder handling.

**EYE PROTECTION:** Select in accordance with the current CSA standard Z94.3,

"Industrial Eye and Face Protection", and any provincial

regulations, local bylaws or guidelines.

**OTHER PROTECTIVE EQUIPMENT:** Metatarsal shoes for cylinder handling. Protective clothing where

needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local

bylaws or guidelines.

## 9. Physical and Chemical Properties

Monoxide Mixture

PHYSICAL STATE: Gas. **FREEZING POINT:** Not avaliable. Not available. **BOILING POINT** Not available. **VAPOUR MOLECULAR WEIGHT:** Not applicable. **PRESSURE** Not applicable. **SPECIFIC SOLUBILITY IN** Not available. Not avaliable. **GRAVITY:** WATER, LIQUID (Water = 1) **SPECIFIC** Not avaliable. **EVAPORATION** Not available. **COEFFICIENT OF** Not applicable. **GRAVITY:** WATER/OIL RATE **DISTRIBUTION: VAPOUR** (Butyl Acetate=1): (air = 1)VAPOUR DENSITY: Not available. % VOLATILES BY Not available. **ODOUR THRESHOLD:** Not available. **VOLUME:** 

APPEARANCE & ODOUR: Colourless gas at Odourless.

normal temperature and pressure.

| The product is stable.   |
|--|
| production of the second of th |
| See Section 7.   |
| None currently known. Gas is chemically inert.   |
| None.  |
| Will not occur.  |
| None currently known.  |
|  |

11. Toxicological Information

See section 3.

## 12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

## 13. Disposal Considerations

WASTE DISPOSAL

Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

**METHOD:** 

#### 14. Transport Information

TDG/IMO SHIPPING NAME:

Compressed gas, n.o.s. (name of the most important inert component).

HAZARD CLASS:

CLASS 2.2: Nonflammable, non-corrosive

flammable, non-corrosive and toxic gas.

UN 1956

**IDENTIFICATION** 

#:

**PRODUCT RQ:** 

Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more

Monoxide Mixture

SHIPPING LABEL(s): Non-flammable, non-corrosive and non-toxic gas

PLACARD (when required) Non-flammable, non-corrosive and non-toxic gas

:

#### SPECIAL SHIPPING INFORMATION:

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

## 15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

DSL (Canada) This product is on the DSL list WHMIS (Canada) CLASS A: Compressed gas.

**International Regulations** 

**EINECS** Not available.

**DSCL** (**EEC**) This product is not classified according to the EU regulations.

International Lists No products were found.

#### 16. Other Information

#### **MIXTURES:**

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

## **HAZARD RATING SYSTEM:**

#### **HMIS RATINGS:**

**HEALTH 0** 

FLAMMABILITY 0

PHYSICAL HAZARD 2

#### STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:

THREADED: CGA-350
PIN-INDEXED YOKE: Not available.
ULTRA-HIGH-INTEGRITY Not available.

**CONNECTION:** 

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

Monoxide Mixture

AV-1 Safe Handling and Storage of Compressed Gas

- P-1 Safe Handling of Compressed Gases in Containers
- P-14 Accident Prevention in Oxygen-Rich, Oxygen-Deficient Atmospheres

SB-2 Oxygen-Deficient Atmospheres

V-1 Compressed Gas Cylinder Valve Inlet and Outlet Connections

V-7 Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures

--- Handbook of Compressed Gases, Fifth Edition

For more indepth information for each component, refer to the pure product MSDS.

The information contained in this MSDS is generated from technical sources using the Chemmate Mixture MSDS system and the pure-product MSDS for each component. These mixtures are not tested as a whole for chemical, physical, or health effects.

#### PREPARATION INFORMATION:

**DATE:** October 15, 2013

**DEPARTMENT:** Safety and Environmental Services

**TELEPHONE:** 905-803-1600

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety nformation, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

Praxair and the Flowing Airstream design are trademarks of Praxair Canada Inc.

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2

Copyright © 2005, Praxair Canada Inc.

Page 7 of 7