

## Praxair Material Safety Data Sheet

### 1. Chemical Product and Company Identification

<b>Product Name:</b> Methyl Bromide	<b>Trade Name:</b> Methyl Bromide
<b>Product Use:</b> Many.	
<b>Chemical Name:</b> Bromomethane	<b>Synonym:</b> Bromomethane, embafume, monobromomethane, R40B1
<b>Chemical Formula:</b> CH <sub>3</sub> Br	<b>Chemical Family:</b> Halogenated Alkane
<b>Telephone:</b> <b>Emergencies:</b> * 1-800-363-0042	<b>Supplier /Manufacture:</b> Praxair Canada Inc. 1 City Centre Drive Suite 1200 Mississauga, ON L5B 1M2
	<b>Phone:</b> 905-803-1600
	<b>Fax:</b> 905-803-1682

*\*Call emergency numbers 24 hours a day only for spills, leaks, fire, exposure, or accidents involving this product. For routine information, contact your supplier or Praxair sales representative.*

### 2. Composition and Information on Ingredients

INGREDIENTS	% (VOL)	CAS NUMBER	LD <sub>50</sub> (Species & Routes)	LC <sub>50</sub> (Rat, 4 hrs.)	TLV-TWA (ACGIH)
Methyl bromide	100	74-83-9	Not available.	302 ppm (Rat, 8 hrs.)	1 ppm

### 3. Hazards Identification



#### Emergency Overview



**DANGER!** Toxic, flammable liquid and gas under pressure. May be fatal if inhaled. Harmful if absorbed through the skin. May cause, lung, liver, kidney, and central nervous system damage. Causes eye and skin burns. Symptoms may be delayed. Can catch fire. Self-contained breathing apparatus must be worn by rescue workers.

#### ROUTES OF EXPOSURE:

Inhalation. Swallowing. Skin absorption. Skin contact. Eye contact.

#### EFFECTS OF A SINGLE (ACUTE) OVEREXPOSURE:

##### INHALATION:

Exposure to vapour is irritating to the respiratory tract with the possibility of pulmonary edema. May cause abdominal pain, nausea, vomiting, blurred vision, headache, mental confusion, and tremors. Additionally may cause liver, kidney, and central nervous system damage with paralysis, convulsion, coma, brain damage, and psychological disturbances.

##### SKIN CONTACT:

Moderate exposure may cause an itching dermatitis seen as local redness, possibly swelling,

and scaling. Severe exposure may cause chemical burns with blister formation. TLV: 5 ppm (OSHA & ACGIH).

---

**SKIN ABSORPTION:** Prolonged or widespread skin contact with the liquid may result in the absorption of harmful amounts of material.

---

**SWALLOWING:** An unlikely route of exposure, but frostbite of the lips and mouth may result from contact with the liquid.

---

**EYE CONTACT:** May cause moderate conjunctivitis, seen as excess redness and swelling of the eye.

---

**EFFECTS OF REPEATED (CHRONIC) OVEREXPOSURE:**

Prolonged or repeated overexposure can cause central nervous system disturbances with blurred vision, numbness, confusion, hallucination, and fainting. Bronchospasm may develop. Repeated skin exposure may result in dermatitis. Although there is no evidence of carcinogenicity in humans, skin contact should be avoided and the product should be handled in well-ventilated areas.

**OTHER EFFECTS OF OVEREXPOSURE:**

None known.

**MEDICAL CONDITIONS AGGRAVATED BY OVEREXPOSURE:**

Inhalation may aggravate asthma and inflammatory or fibrotic pulmonary disease. Because of its irritating properties, this material may aggravate an existing dermatitis.

**SIGNIFICANT LABORATORY DATA WITH POSSIBLE RELEVANCE TO HUMAN HEALTH HAZARD EVALUATION:**

This material has been shown to cause cancer in laboratory animals by repeated exposure through stomach intubation in rats. Also, this material has been shown to cause mutations in bacteria. There is insufficient evidence to evaluate the carcinogenicity of this material in humans.

**CARCINOGENICITY:**

Classified + (Proven.) by NIOSH. A4 (Not classifiable for human or animal.) by ACGIH, 3 (Not classifiable for human.) by IARC, D (Not classifiable for human or animal.) by EPA.

<b>4. First Aid Measures</b>
------------------------------

**INHALATION:**

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately. Keep patient warm.

**SKIN CONTACT:**

Immediately flush affected areas with water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician.

**SWALLOWING:**

This product is a gas at normal temperature and pressure.

**EYE CONTACT:**

For contact with the liquid, immediately flush eyes thoroughly with warm water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. See a physician, preferably an ophthalmologist, immediately.

**NOTES TO PHYSICIAN:**

*Symptoms may be delayed, with latency from 30 minutes to several days. Neurological symptoms may appear in most cases of overexposure. There is no specific antidote. Treatment of over-exposure should be directed at the control of symptoms and the clinical condition.*

## 5. Fire Fighting Measures

**FLAMMABLE :** Yes. **IF YES, UNDER WHAT CONDITIONS?** Forms explosive mixtures with air and oxidizing agents.

<b>FLASH POINT (test method)</b> Flammable gas.	<b>AUTOIGNITION TEMPERATURE</b> 536.7°C (998.1°F)
---	---

<b>FLAMMABLE LIMITS IN AIR, % by volume:</b>	<b>LOWER:</b> 10	<b>UPPER:</b> 16
--	------------------	------------------

### EXTINGUISHING MEDIA:

CO<sub>2</sub>, dry chemical, water spray or fog.

### SPECIAL FIRE FIGHTING PROCEDURES:

**DANGER!** Evacuate all personnel from danger area. Do not approach area without self-contained breathing apparatus and protective clothing. Immediately cool containers with water spray from maximum distance taking care not to extinguish flames. Remove ignition sources if without risk. If flames are accidentally extinguished, explosive re-ignition may occur; therefore, appropriate measures should be taken; e.g., total evacuation. Re-approach with extreme caution. Reduce corrosive vapours with water spray or fog. Stop flow of gas if without risk while continuing water spray. Remove all containers from area if without risk. Allow fire to burn out.

### UNUSUAL FIRE AND EXPLOSION HAZARD:

Forms explosive mixture with air and oxidizing agents. Container may rupture due to heat of fire. Do not extinguish flames due to possibility of explosive re-ignition. Toxic, flammable, corrosive vapours may spread from spill. Toxic, explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with appropriate device. Vapours are irritating. Contact may cause burns to skin and eyes. No part of a container should be subjected to a temperature higher than 52 C.

### HAZARDOUS COMBUSTION PRODUCTS:

These products are carbon oxides (CO, CO<sub>2</sub>), halogenated compounds.

### SENSITIVITY TO IMPACT:

Avoid impact against container.

### SENSITIVITY TO STATIC DISCHARGE:

Possible - ground equipment before use.

## 6. Accidental Release Measures

### STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

**DANGER!** DANGER: Toxic, flammable, liquefied gas under pressure. May be fatal if inhaled. Gas cannot always be detected by odour. Do not breathe gas. Do not get liquid or vapour in eyes, on skin or clothing. Safety showers and eye wash fountains should be immediately available. Use piping and equipment adequately designed to withstand pressures to be encountered. May form explosive mixtures with air. Keep away from heat, sparks, and open flame. Ground all equipment. Only use spark-proof tools and explosion-proof equipment. When returning cylinder, install valve outlet plug tightly. Keep away from oxidizing agents. Reverse flow into cylinder may cause rupture. Use a check valve or other protective apparatus in any line or piping from the cylinder to prevent reverse flow.

### WASTE DISPOSAL METHOD:

Prevent waste from contaminating the surrounding environment. Keep personnel away. Discard any product, residue, disposable container, or liner in an environmentally acceptable manner, in full compliance with federal, provincial, and local regulations. If necessary, call your local supplier for assistance.

## 7. Handling and Storage

### PRECAUTIONS TO BE TAKEN IN STORAGE:

Store and use with adequate ventilation. Separate flammable cylinders from oxygen, chlorine, and other oxidizers by at least 6 m or use a barricade of non-combustible material. This barricade should be at least 1.5 m high and have a fire resistance rating of at least ½ hour. Firmly secure cylinders upright to keep them from falling or being knocked over. Screw valve protection cap firmly in place by hand. Post "No Smoking or Open Flames" signs in storage and use areas. There must be no sources of ignition. All electrical equipment in storage areas must be explosion-proof. Storage areas must meet national electric codes for Class 1 hazardous areas. Store only where temperature will not exceed 52 C. Store full and empty cylinders separately. Use a first-in, first-out inventory system to prevent storing full cylinders for long periods.

### PRECAUTIONS TO BE TAKEN IN HANDLING:

Protect cylinders from damage. Use a suitable hand truck to move cylinders; do not drag, roll, slide, or drop. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. Never insert an object (e.g., wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Open valve slowly. If valve is hard to open, discontinue use and contact your supplier. For other precautions, see Section 16.

For additional information on storage and handling, refer to Compressed Gas Association (CGA) pamphlet P-1, *Safe Handling of Compressed Gases in Containers*, available from the CGA. Refer to Section 16 for the address and phone number along with a list of other available publications.

### OTHER HAZARDOUS CONDITIONS OF HANDLING, STORAGE, AND USE:

**Toxic, flammable, corrosive liquid and gas under pressure.** May be fatal if inhaled. Do not breathe gas. Do not get liquid or vapours in eyes, on skin, or clothing. Safety showers and eyewash fountains should be immediately available. Use only in a closed system constructed of corrosion resistant materials. Use piping and equipment adequately designed to withstand pressures to be encountered. Use only spark-proof tools and explosion-proof equipment. Keep away from heat, sparks, and open flame. **May form explosive mixtures with air.** Ground all equipment. Store and use with adequate ventilation at all times. Close valve after each use; keep closed even when empty. **Prevent reverse flow.** Reverse flow into cylinder may cause rupture. Use a check valve or other protective device in any line or piping from the cylinder. **When returning cylinder to supplier,** be sure valve is closed, then install valve outlet plug tightly. **Never work on a pressurized system.** If there is a leak, close the cylinder valve. Vent the system down in a safe and environmentally sound manner in compliance with all federal, provincial, and local laws; then repair the leak. **Never place a compressed gas cylinder where it may become part of an electrical circuit.**

## 8. Exposure Controls/Personal Protection

### VENTILATION/ENGINEERING CONTROLS:

**LOCAL EXHAUST:** A corrosion-resistant system is acceptable.  
Use to maintain exposure below applicable limits.

**MECHANICAL (general):** Inadequate.  
See SPECIAL.

**SPECIAL:** Use only in a closed system.  
A corrosion-resistant, forced-draft fume hood is preferred.

**OTHER:** Not available.

### PERSONAL PROTECTION:

**RESPIRATORY PROTECTION:** Use respirable fume respirator or air supplied respirator when working in confined space or where local exhaust or ventilation does not keep exposure below TLV. Select in accordance with the provincial regulations or guidelines. Selection should also be based on the current CSA standards Z94.4, "Selection, care and use of respirators". Respirators should be approved by NIOSH and MSHA.

**SKIN PROTECTION:** VITON (Rubber and leather are unsatisfactory).

**EYE PROTECTION:** Wear safety glasses when handling cylinders.

Select in accordance with the current CSA standard Z94.3, "Industrial Eye and Face Protection", and any provincial regulations, local bylaws or guidelines.

**OTHER PROTECTIVE EQUIPMENT:** Metatarsal shoes for cylinder handling. Protective clothing where needed. Cuffless trousers should be worn outside the shoes. Select in accordance with the current CSA standard Z195, "Protective Foot Wear", and any provincial regulations, local bylaws or guidelines.

## 9. Physical and Chemical Properties

<b>PHYSICAL STATE:</b> Gas. (Compressed Gas.)	<b>FREEZING POINT:</b> -94°C (-137.2°F)	<b>pH:</b>	Not applicable.
<b>BOILING POINT:</b> 3.55°C (38.4°F)	<b>VAPOUR PRESSURE:</b> 166.6 kPa (@ 20°C)	<b>MOLECULAR WEIGHT:</b>	94.95 g/mole
<b>SPECIFIC GRAVITY: LIQUID ( Water = 1)</b> 1.732 @ 0 C	<b>SOLUBILITY IN WATER:</b> Negligible.		
<b>SPECIFIC GRAVITY: VAPOUR (air = 1)</b> 3.355	<b>EVAPORATION RATE (Butyl Acetate=1):</b> >1 compared to (Butyl Acetate = 1)	<b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b>	Not applicable.
<b>VAPOUR DENSITY:</b> 0.00397 g/ml @ 25 C	<b>% VOLATILES BY VOLUME:</b> 100% (v/v).	<b>ODOUR THRESHOLD:</b>	Not available.

**APPEARANCE & ODOUR:** Colourless.

Odour: Chloroform-like at high concentrations.

## 10. Stability and Reactivity

<b>STABILITY:</b>	The product is stable.
<b>CONDITIONS OF CHEMICAL INSTABILITY:</b>	Not available.
<b>INCOMPATIBILITY (materials to avoid):</b>	Zinc, magnesium, aluminum and their alloys, ammonia, dimethylsulfoxide, ethylene oxide, acetylenic compounds, hot metal surfaces, oxidizers.
<b>HAZARDOUS DECOMPOSITION PRODUCTS:</b>	Thermal decomposition or burning may produce carbon monoxide/carbon dioxide and highly toxic fumes of bromides.
<b>HAZARDOUS POLYMERIZATION:</b>	Will not occur.
<b>CONDITIONS OF REACTIVITY:</b>	None known.

## 11. Toxicological Information

See section 3.

## 12. Ecological Information

No adverse ecological effects expected. This product does not contain any Class I or Class II ozone-depleting chemicals. The components of this mixture are not listed as marine pollutants by TDG Regulations.

## 13. Disposal Considerations

**WASTE DISPOSAL METHOD:** Do not attempt to dispose of residual or unused quantities. Return cylinder to supplier.

## 14. Transport Information

**TDG/IMO SHIPPING NAME:** Methyl Bromide

<b>HAZARD CLASS:</b>	CLASS 2.3: Toxic gas.	<b>IDENTIFICATION #:</b>	UN1062	<b>PRODUCT REPORTABLE QUANTITY (PROQ):</b>
				Any accidental release in a quantity that could pose a danger to public safety or any sustained release of 10 minutes or more.

**SHIPPING LABEL(s):** Toxic gas

**PLACARD (when required):** Toxic gas

**SPECIAL SHIPPING INFORMATION:**

Cylinders should be transported in a secure position, in a well-ventilated vehicle. Cylinders transported in an enclosed, non-ventilated compartment of a vehicle can present serious safety hazards.

## 15. Regulatory Information

The following selected regulatory requirements may apply to this product. Not all such requirements are identified. Users of this product are solely responsible for compliance with all applicable federal, provincial, and local regulations.

**DSL (Canada)** This product is on the DSL list

**WHMIS (Canada)**

CLASS A: Compressed gas.  
 CLASS B1: Flammable gas.  
 CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC)   
 CLASS D-2A: Material causing other toxic effects (VERY TOXIC)   
 CLASS D-2B: Material causing other toxic effects (TOXIC).

**International Regulations**

**EINECS** Not available.

**DSCL (EEC)** R23- Toxic by inhalation.  
R45- May cause cancer.

**International Lists** No products were found.

## 16. Other Information

**MIXTURES:**

When two or more gases, or liquefied gases are mixed, their hazardous properties may combine to create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an Industrial Hygienist, or other trained person when you make your safety evaluation of the end product. Remember, gases and liquids have properties which can cause serious injury or death.

**HAZARD RATING SYSTEM:**

**HMIS RATINGS:**

HEALTH 2 \*

FLAMMABILITY 4

PHYSICAL HAZARD 2

\*An Asterisk used in conjunction with HMIS health hazards ratings designates a carcinogenic or reproductive hazard.

**STANDARD VALVE CONNECTIONS FOR U.S. AND CANADA:**

<b>THREADED:</b>	CGA-330
<b>PIN-INDEXED YOKE:</b>	Not available.
<b>ULTRA-HIGH-INTEGRITY CONNECTION:</b>	No current assignment.

Use the proper CGA connections. **DO NOT USE ADAPTERS.** Additional limited-standard connections may apply. See CGA pamphlets V-1 and V-7 listed below.

Ask your supplier about free Praxair safety literature as referred to in this MSDS and on the label for this product. Further information about this product can be found in the following pamphlets published by the Compressed Gas Association, Inc. (CGA), 4221 Walney Road, 5th Floor, Chantilly, VA 20151-2923, Telephone (703) 788-2700, Fax (703) 961-1831, website: www.cganet.com.

AV-1	Safe Handling and Storage of Compressed Gas
P-1	Safe Handling of Compressed Gases in Containers
V-1	Compressed Gas Cylinder Valve Inlet and Outlet Connections
V-7	Standard Method of Determining Cylinder Valve Outlet Connections for Industrial Gas Mixtures
---	Handbook of Compressed Gases, Fifth Edition

**PREPARATION INFORMATION:**

<b>DATE:</b>	<b>October 15, 2013</b>
<b>DEPARTMENT:</b>	<b>Safety and Environmental Services</b>
<b>TELEPHONE:</b>	<b>905-803-1600</b>

The opinions expressed herein are those of qualified experts within Praxair Canada Inc. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the conditions of use of the product are not within the control of Praxair Canada Inc., it is the user's obligation to determine the conditions of safe use of the product.

Praxair Canada Inc. requests the users of this product to study this Material Data Sheet (MSDS) and become aware of product hazards and safety information. To promote safe use of this product, a user should (1) notify its employees, agents and contractors of the information on this MSDS and any product hazards and safety information, (2) furnish this same information to each of its customers for the product, and (3) request such customers to notify their employees and customers for the product of the same product hazards and safety information.

*Praxair and the Flowing Airstream design are trademarks of Praxair Canada Inc.*

Other trademarks used herein are trademarks or registered trademarks of their respective owners.



Praxair Canada Inc.  
1 City Centre Drive  
Suite 1200  
Mississauga, ON L5B 1M2