31 Incorporated P.O. Box 278 Newcomerstown, OH 43832 USA (740) 498-8324

MATERIAL SAFETY DATA SHEET

24 Hour Emergency Service: CHEM•TEL INC. (800) 255-3924

I. IDENTIFICATION

PRODUCT NAME:	X-tra Slik Bead Lubricant # 1010012	
CHEMICAL NAME:	N/A	CHEMICAL FAMILY: Glycols
FORMULA:	N/A	MOLECULAR WEIGHT: NA
SYNONYMS:	Propanediol, 1.2 Dihyroxypropanf	
DEPARTMENT OF:	None	HAZARD CLASSIFICATION NOS. None
TRANSPORTATION:		SHIPPING NAME: Water Base Soap
CAS#:	None	CAS NAME: NA

II. PHYSICAL DATA

BOILING POINT:N/ASPECIFIC GRAVITY:N/AVAPOR DENSITY:N/APERCENT VOLATILES BY VOLUME:N/AAPPEARANCE AND ODOR:N/A

FREEZING POINT: N/A VAPOR PRESSURE AT 20° C.: N/A EVAPORATION RATE: N/A SOLUBILITY IN WATER (% BY WEIGHT): 100#

III. INGREDIENTS

MATERIAL	% T	TLV UNITS HAZARD	CAS#
Water	80 - 90%	N/A	N/A
Monoethanolamine	.0203%	may cause minor irritation	141-43-5
Propylene Glycol	.0102%	may cause minor irritation	57-55-6
Tamadol 91	.0102%	may cause minor irritation	68551-12-2

IV. FIRE AND EXPOSURE HAZARD DATA

FLASH POINT (TEST METHODS): None FLAMMABLE LIMITS IN AIR (% BY VOLUME): NA LOWER: N/A ; UPPER: N/A EXTINGUISHING MEDIA: CO₂Dry Chemical

SPECIAL FIRE FIGHTING PROCEDURES: Don't enter fire without proper protection

UNUSUAL FIRE & HAZARD EXPLOSION HAZARDS: None

31 Incorporated P.O. Box 278 Newcomerstown, OH 43832

X-tra Slik Bead Lubricant # 1010012

(740) 498-8324

Page 2

V. EMERGENCY & FIRST AID PROCEDURES

EXPOSURE LIMITS TLV, PEL, AND SOURCE: See Section III ACUTE EFFECTS OF OVEREXPOSURE: SWALLOWING: No significant signs or symptoms any health problems. If swallowed, Do Not induce vomiting, give large amounts of water and milk SKIN ABSORPTION: No significant signs or symptoms indicative of any health hazard. Always use good hygiene practices after handling. No significant signs or symptom; if breathing hard get to fresh air INHALATION: If clothing becomes saturated, remove and shower with soap and water. Discard SKIN CONTACT: all contaminated clothing. EYE CONTACT: If splashed in eyes flush with water 20-30 min, retract eyelids often. Seek medical attention if redness, tears persist. CHRONIC EFFECTS OF OVEREXPOSURE: None expected OTHER HEALTH HAZARDS: Handling: Use eye protection. Use good personal hygiene measures. Wash with soap and water after use or before eating. Etc.

VI. REACTIVITY DATA

STABILITY UNSTABLE: STABLE: X CONDITIONS TO AVOID: INCOMPATIBILITY (MATERIALS TO AVOID): HAZARDOUS COMBUSTION OR DECOMPOSITION PRODUCTS:

HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: X If spille

CONDITIONS TO AVOID: If spilled, slippery conditions may occur

Goggles

VII. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Clean with absorbent and discard per local, state and federal regulations.

WASTE DISPOSAL METHOD:

VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (SPECIFY TYPE): NoneVENTILATION: good practice when usingPROTECTIVE GLOVES:NoneEYE PROTECTION:OTHER PROTECTIVE EQUIPMENT:None

31 Incorporated P.O. Box 278 Newcomerstown, OH 43832

X-tra Slik Bead Lubricant # 1010012

(740) 498-8324

IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Clean up spills, keep container closed, keep away from direct heat.

OTHER PRECAUTIONS:

None

X. CARCINOGEN EVALUATION

None

XI. MSDS PREPARATION INFORMATION

THIS MSDS WAS PREPARED BY:

Charles Muhs Technical Advisor 31 Incorporated 100 Enterprise Drive Newcomerstown, OH 43832

THIS MSDS WAS LAST UPDATED ON: (Date) Jan. 1, 2010

XII. HMIS RATING

HEALTH:	FLAMMABILITY:	REACTIVITY:	PERSONAL PROTECTIVE EQUIP.:
0	1	0	Stated in above

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY THE MATERIALS IF REASONABLE SAFETY PROCEDURES ARE NOT ADHERED TO AS STIPULATED IN THE DATA SHEET. ADDITIONALLY, VENDOR ASSUMES NO RESPONSIBILITY FOR INJURY TO VENDEE OR THIRD PERSONS PROXIMATELY CAUSED BY ABNORMAL USE OF THE MATERIAL, EVEN IF REASONABLE SAFETY PROCEDURES ARE FOLLOWED. FURTHERMORE, VENDEE ASSUMES THE RISK IN HIS USE OF THE MATERIAL.

Page 3